Automated Bug Report Field Reassignment and Refinement Prediction

Xin Xia, Member, IEEE, David Lo, Member, IEEE, Emad Shihab, and Xinyu Wang

Abstract-Bug fixing is one of the most important activities in software development and maintenance. Bugs are reported, recorded, and managed in bug tracking systems such as Bugzilla. In general, a bug report contains many fields, such as product, component, severity, priority, fixer, operating system (OS), and platform, which provide important information for the bug triaging and fixing process. Our previous study finds that approximately 80% of bug reports have their fields reassigned and refined at least once, and bugs with reassigned and refined fields take more time to fix than bugs with no reassigned and refined fields. Thus, automatically predicting which bug report fields get reassigned and refined could help developers to save bug fixing time. Considering that a bug report could have multiple field reassignments and refinements (e.g., the product, component, fixer, and other fields of a bug report can get reassigned and refined), in this paper, we propose a multi-label learning algorithm to predict which bug report fields might be reassigned and refined. We note that the number of bug reports with some types of reassignment and refinement (e.g., bugs whose severity fields gets reassigned and refined) is a small proportion of the whole bug report collection, indicating the class imbalance problem. Thus, we propose imbalanced ML.KNN (Im-ML.KNN), which extends ML.KNN, one of the state-of-the-art multi-label learning algorithms, to achieve better performance. Im-ML.KNN is a composite model that combines 3 multi-label classifiers built using different types of features (i.e., meta, textual, and mixed features). We evaluate our solution on 4 large bug report datasets including OpenOffice, Netbeans, Eclipse, and Mozilla containing a total of 190,558 bug reports. We show that Im-ML.KNN can achieve an average F-measure score of 0.56-0.62. We also compare Im-ML.KNN with other state-of-art methods, such as the method proposed by Lamkanfi et al., ML.KNN, and HOMER-NB. The results show that Im-ML.KNN, on average, improves the average F-measure scores of Lamkanfi et al.'s method, ML.KNN, and HOMER-NB by 119.69%, 9.11%, and 161.08%, respectively.

Index Terms—Bug report field reassignment and refinement (BRFRR), composite model, imbalance learning, multi-label learning.

Manuscript received August 30, 2014; revised December 27, 2014 and March 22, 2015; accepted September 18, 2015. Date of publication October 26, 2015; date of current version August 30, 2016. This work was supported in part by the National Basic Research Program of China (the 973 Program) under Grant 2015CB352201, the National Key Technology R&D Program of the Ministry of Science and Technology of China under Grant 2014BAH24F02, and the Fundamental Research Funds for the Central Universities. Associate Editor: W. E. Wong. (Corresponding author: Xinyu Wang.)

X. Xia and X. Wang are with the College of Computer Science and Technology, Zhejiang University, Hangzhou 310000, China (e-mail: xxia@zju.edu.cn; wangxinyu@zju.edu.cn).

D. Lo is with the School of Information Systems, Singapore Management University, 188065 Singapore (e-mail: davidlo@smu.edu.sg).

E. Shihab is with the Department of Computer Science and Software Engineering, Concordia University, Montreal, QC H4B 1R6, Canada (e-mail: es-hihab@cse.concordia.ca).

Color versions of one or more of the figures in this paper are available online at http://ieeexplore.ieee.org.

Digital Object Identifier 10.1109/TR.2015.2484074

ACRONYMS AND ABBREVIATIONS

| BRFRR | Bug report field reassignment and refinement. |
|-----------|---|
| Im-ML.KNN | Imbalanced ML.KNN. |
| NB | Naive Bayes. |
| KNN | K-nearest neighbors. |
| LDS | Longitudinal data setup. |

NOTATION

| BR | Set of bug report collection. |
|------------------------|---------------------------------------|
| b_i | <i>i</i> th bug report. |
| $w_{i,j}$ | Weight for j th term in b_i . |
| L | Set of labels. |
| $\mathrm{threshold}_l$ | Threshold for label <i>l</i> . |
| P_l | Precision for label <i>l</i> . |
| R_l | Recall for label <i>l</i> . |
| F_l | Precision for label <i>l</i> . |
| Ave.P | Average precision for labels in L . |
| Ave.R | Average Recall for labels in L |
| Ave.F | Average F-measure for labels in L. |
| Sample | Sample size. |
| Meta | Meta features. |
| Text | Textual features. |
| Mixed | Mixed features. |

I. INTRODUCTION

UGS are inevitable in the whole lifecycle of software de-D velopment and maintenance, and bug fixing is a time-consuming and costly task. Previous studies from NIST show that software bugs cost the US economy an estimated \$59 billion every year, which is around 0.6% of the gross domestic product [1]. Bug tracking systems such as Bugzilla are used to report, record, and manage these bugs. A typical bug report contains many fields, e.g., the summary and description fields which provide the textual description of the observed bug, the status field which shows the current status (e.g., closed or resolved), the product and component fields where the bug is detected, the priority and severity fields which mark the importance of the bug, the version, operating system (OS), and platform fields which indicate the runtime environment affected by the bug, and the reporter and fixer fields. These fields are vital for developers to triage and fix the bug [2], [3].

0018-9529 © 2015 IEEE. Personal use is permitted, but republication/redistribution requires IEEE permission. See http://www.ieee.org/publications standards/publications/rights/index.html for more information.

However, Bug report fields often get reassigned and refined. Various types of bug report field reassignments and refinements have been investigated in the literature. Shihab et al. study reopened bugs, and they find that, for Eclipse Platform 3.0, the average time to resolve a reopened bug is more than twice the time to resolve a non-reopened bug [4], [5]. Lamkanfi and Demeyer studied component reassignments and found that, for Mozilla, it takes a long time to reassign a bug report to the correct component [6]. Jeong *et al.* studied fixer reassignments and refinements in Eclipse and Mozilla and found that 37%-44% of bugs have their fixer reassigned and refined [7]. Saha et al. found that 10% of long-lived bugs get their fixers reassigned and refined five or more times [8]. In our previous work, we analyzed bug reports from OpenOffice, Netbeans, Eclipse, and Mozilla and found that approximately 80% of bug reports have their fields reassigned [9]. Also, we found that bug reports with field reassignments have statistically significantly longer bug fix time than those without reassignments.

The aforementioned studies indicate that bug reassignments and refinements are associated to longer bug fixing times. Some fields are wrongly assigned and this can result in a delay for a bug to get resolved, while other fields are not inherently wrong, but need to be adjusted with additional insights that bug triagers have after they analyze the bugs [10]. For these cases, there is a need for an approach that can help developers reduce the amount of incorrect assignments or to suggest appropriate refinements that developers can consider to make in the future. Such an approach can reduce the number of unnecessary reassignments and refinements. Admittedly, since many factors affect bug fixing time (e.g., difficulty to reproduce and resolve a bug [8]), such an approach is not a panacea to make bug fixing time short. Nevertheless, it helps solve a problem that impacts bug fix time.

To address the above-mentioned need, in this paper, we develop a tool that leverages *multi-label learning* algorithms to automatically predict which bug report fields will be reassigned or refined. In the multilabel learning literature, one data instance (i.e., a bug report) can be assigned to multiple labels (i.e., fields that are predicted to be reassigned and refined) [11]. It is important to note that our work complements previous studies such as the work on reopened bug prediction [4], [5] and component reassignment and refinement prediction [6], [12], since our work generalizes these studies by considering the reassignments and refinements of many different fields in a bug report. Our proposed multi-label learning algorithm can predict, not only the reassignment and refinement of the status field or the component field, but also all other fields simultaneously.1 To investigate the usefulness of our tool, we have checked with several experienced developers from OpenOffice and NetBeans Project Management Committee, who have fixed hundreds of bugs and managed the bug reports in OpenOffice and Netbeans. Some of their comments are given here.

"Considering a lot of "raw" users would submit bug reports in our community, there would be many errors (wrongly assigned fields in the bug report), the tool would be possible to evaluate a "raw" user submitted report and predict what fields will be changed."

"Although human thought was necessary here to decide what the right component (fields) should be (during bug fixing process), a tool which assists whether a fields would get reassigned and refined still relief the workload for a developer."

"I think, a reassignment prediction can be useful, especially when non-developers create bug requests that are not familiar with the development process and management. Such users may fill out some fields incorrectly, which could be detected more easily and help the developers to better assess and organize the reports."

To build our tool, we extract the values of important features from the bug reports when they are initially submitted. The features extracted from a training set of bug reports, along with field reassignment and refinement information, are then used to build a multi-label classifier. We extract field reassignment and refinement information by analyzing the history of bug reports to identify fields that are changed after the bug report was initially submitted. The resultant multi-label classifier serves as a tool and will be used to predict the fields which would get reassigned and refined for a new submitted bug report. The output of our tool is a list of bug report fields which would get reassigned and refined. With our tool, developers will be better informed on whether they have assigned the right field values when they submit a bug report.

To assist in making accurate predictions, one possible solution is to use ML.KNN [13], one of the state-of-the-art algorithms used to solve the multi-label learning problem. However, we find that for many fields, there is only a very small percentage of bug reports whose fields are reassigned and refined. For example, in Eclipse, only 9.76%, 18.44%, 9.19%, and 8.14% of bug reports have their product, component, severity, and status fields reassigned and refined [9]. We refer to this phenomenon as the class imbalance phenomenon [14]. To improve the overall performance of ML.KNN, we propose imbalanced ML.KNN (Im-ML.KNN), which addresses the class imbalance phenomenon experienced in the bug report field reassignment and refinement task. Im-ML.KNN is a composite model, which combines three multilabel classifiers built using different types of features (i.e., meta, textual, and mixed features). In our paper, meta features refer to the nontextual fields of a bug report, e.g., reporter, assignee, product, component, etc, textual features refer to the proceed terms extracted from the description and summary field, and mixed features refer to the combination of both meta and textual features. Im-ML.KNN automatically learns the best threshold value to predict which fields will be reassigned and refined in the training data. By default, we set the number of neighbors K in Im-ML.KNN as 10.

In our previous study, we perform an empirical study on bug report field reassignment and refinement [9]. This paper com-

¹In the machine learning literature, the problems of reopened bug prediction and component prediction can be mapped to single-label learning problems. Single-label learning is a classification problem where one instance (e.g., a bug report) can only be assigned to one label (e.g., reopened or not reopened, and reassigned and refined or not reassigned and refined.)

plements our previous work, and our previous work serves as a motivation to this work. In particular, in this paper, we propose an automated tool to predict which bug report fields will get reassigned to help developers reduce bug fixing effort.

We evaluate our *Im-ML.KNN* algorithm on bug report datasets from four large open source porjects namely—OpenOffice, Netbeans, Eclipse, and Mozilla, containing a total of 190 558 bug reports. The experiment results show that *Im-ML.KNN* can achieve an average F-measure score between 0.52–0.67. We also compare *Im-ML.KNN* with other state-of-the-art methods, such as the method proposed by Lamkanfi *et al.*, ML.KNN and HOMER-NB [15]. We address the following research questions.

1) What is the F-measure of *Im-ML.KNN*? How much improvement can it achieve over the method proposed by Lamkanfi *et al.* [6], ML.KNN [13], and HOMER-NB [15]?

The results show that Im-ML.KNN, on average, improves the F-measure score of Lamkanfi *et al.*'s method, ML.KNN, and HOMER-NB by 119.69%, 9.11%, and 161.08%, respectively.

2) Can the F-measure of Im-ML.KNN outperform those of its constituent components (i.e., meta classifier, text classifier, and mixed classifier)?

Yes, Im-ML.KNN improves the average F-measure scores of meta classifier, text classifier, and mixed classifier by 8.91%, 164.31%, and 9.11%, respectively. The results show that it is beneficial to combine the 3 classifiers.

3) Do different numbers of neighbors affect the F-measure of *Im-ML.KNN*?

No, across the four projects, Im-ML.KNN achieves a relatively stable performance when different numbers of neighbors are used.

4) What are good predictors of bug report field reassignments and refinements? Do the predictors differ for different fields?

Meta features (e.g., *product, component, assignee*) make up most of the top-10 features. Among the four projects, product, component, reporter, and assignee are the four most important meta features related to various types of field reassignment.

5) What is the effect of varying the amount of training data on the effectiveness of *Im-ML.KNN*?

To reduce the amount of training data, we perform ten times K-fold cross validation, with K varied from 2 to 10. When we vary K from 10 to 2, the F-measures for Eclipse, Mozilla, and Firefox remains relatively stable (it fluctuates less than 5.68% from the original value). For OpenOffice, the F-measure reduces by 26.81% when we vary k from 10 to 2.

6) How much time does it take for Im-ML.KNN to run? The average model building time and the average prediction time of Im-ML.KNN is 0.0265 and 0.0158 s per bug report, respectively.

The main contributions of this paper are given here.

• Propose a new algorithm that effectively deals with the class imbalance problem. Considering the class imbalance phenomenon, we propose a new algorithm named imbalanced ML.KNN (*Im-ML.KNN*) to achieve better performance when predicting reassigned and refined fields.

- Accurately predict which bug fields will be reassigned and refined. We propose a multilabel learning algorithm to accurately predict which bug fields will be reassigned and refined. To the best of our knowledge, this is the first study to use *multi-label learning* to predict bug report field reassignments and refinements.
- Perform an extensive empirical study to examine the effectiveness of *Im-ML.KNN* in predicting which bug fields will be reassigned and refined. We investigate the performance of *Im-ML.KNN* on four large open-source projects, and the experiment results show that our method improves existing state-of-the-art methods such as Lamkanfi *et al.*'s method and ML.KNN.

The remainder of this paper is organized as follows. We describe the preliminary materials in Section II. We outline the overall framework of our bug report field reassignment and refinement prediction solution in Section III. We elaborate how the features and labels (i.e., various bug report field reassignments and refinements) are extracted from bug reports in Section IV. We present our multi-label classification approach *Im-ML.KNN* in Section V. We report the experiment results in Section VI. We discuss and present the threats to validity of our paper in Section VII and VIII. We describe related work in Section IX. We conclude and mention future work in Section X.

II. PRELIMINARIES

Here, we first present the background of bug report field reassignment and refinement in Section II-A. Next, we describe ML.KNN, which is the state-of-the-art multilabel classification algorithm on which we build our approach, in Section II-B.

A. Background

A typical bug report contains many useful fields, such as product, component, fixer, summary, and description. However, in some cases, the fields in the bug report get reassigned and refined. Fig. 1 shows a bug report from Eclipse with BugID 221068.2 We notice that the product, component, fixer, and status fields of this bug report have been reassigned and refined. The product was reassigned from WTP Incubator to WTP Source Editing, and the component was reassigned from incubator to wtp.inc.xsl, and finally it was reassigned to wst.xsl. The fixer was reassigned from wtp.inc-inbox to doug.satchwell. Moreover, the bug report in Fig. 1 was also a reopened bug, i.e., the bug report was first resolved and fixed by doug.satchwell, and then d a carver reopened it and changed the status to new. In this paper, we only consider one type of *status* reassignment: resolved or closed to reopen. This is the one of most important reassignment and refinement. We ignore the other status reassignments and refinements as in general a bug report status would eventually get changed (e.g., from open to closed) as developers are working to fix it.

²[Online]. Available: https://bugs.eclipse.org/bugs/show_bug. cgi?id=221068

| Bug 221068 - [xslt][launcher] XSL Parameter variables that use Eclipse Va | ariables don't |
|---|----------------|
|---|----------------|

| Status: RESOLVED FIXED Product: WTP Source Editing <u>Component</u> : wst.xsl Version: unspecified Platform: PC All | Importance: P3 normal (<u>vote</u>) Target Milestone: 3.1 <u>Assigned To</u> : Doug QA Contact: David Williams | Reported: 2008-03-02 12:37 EST by David Carv Modified: 2009-04-30 14:25 EDT (<u>History</u>) CC List: 1 user (<u>show</u>) |
|---|--|--|
| David Carver 2008-03-02 12:37 | :31 EST | |
| When setting up a launc use an eclipse variable expanded first. This (i.e. if {workspace_loc | <pre>h configuration, and tryi , the eclipse variable is causes the wrong or unexp } is selected as the ecli d through to the XCIM</pre> | ng to set an XSLT parameter to passed through without being ected value to be sent in. pse variable. the text |

| Who | When | What | Removed | Added |
|----------------|-------------------------|------------------|---------------|--------------------|
| doug.satchwell | 2008-03-10 15:47:26 EDT | сс | | doug.satchwell |
| | | Status | NEW | RESOLVED |
| | | Resolution | | FIXED |
| | | Target Milestone | | 0.5 M6 |
| d_a_carver | 2008-03-10 16:12:53 EDT | Status | RESOLVED | REOPENED |
| | | Resolution | FIXED | |
| d_a_carver | 2008-03-10 16:13:36 EDT | Assignee | wtp.inc-inbox | doug.satchwell |
| | | Status | REOPENED | NEW |
| d_a_carver | 2008-03-10 16:13:46 EDT | Status | NEW | ASSIGNED |
| d_a_carver | 2008-03-10 16:14:14 EDT | Status | ASSIGNED | RESOLVED |
| | | Resolution | | FIXED |
| d_a_carver | 2008-06-05 21:40:41 EDT | Component | incubator | wtp.inc.xsl |
| webmaster | 2009-03-31 10:56:33 EDT | Component | wtp.inc.xsl | wst.xsl |
| | | Product | WTP Incubator | WTP Source Editing |
| | | Target Milestone | 0.5 M6 | |
| d_a_carver | 2009-04-30 14:25:06 EDT | Target Milestone | | 3.1 |

Fig. 1. Reassigned and refined Bug Report of Eclipse Project with BugID 221068.

Observations and Implications. From the above bug report, we make the following observations:

- The bug report was created on March 2nd, 2008, and it was fixed on April 30th, 2009. This bug took approximately one year to get fixed.
- 2) The component was reassigned from incubator to wtp.inc.xsl on June 5th, 2008, by d_a_carver. However, on March 31st, 2009, webmaster still reassigned its component and product fields. Thus, it seems that even though nine months had passed, a suitable person to fix the bug was still to be found.

B. Multilabel Learning

Multilabel learning refers to the task of assigning one or more labels to a data instance. Traditional classification only assigns one label to an instance. However, in many situations, one instance could have more than one label. In our bug report field reassignment and refinementprediction problem, one bug report could have several of its fields reassigned and refined. For example, in Fig. 1, the bug report has four types of field reassignments and refinements, i.e., product, component, fixer, and status field reassignments and refinements.

Formally, multilabel learning is defined as follows. Let χ denotes the input space (i.e., bug report collection) and let L denote the set of labels (i.e., eight types of bug report field reassignment and refinement). Given a multi-label training dataset $D = \{(X_i, Y_i)\}_{i=1}^n$, where $X_i \in \chi$ denotes a bug report, and $Y_{X_i} = \{0, 1\}^{|L|} (Y_{X_i}(l) = 1$ indicates that the bug report X_i is assigned to the *l*th label (i.e., one of the field reassignment and refinement types) and $Y_{X_i}(l) = 0$ indicates otherwise), the goal of multi-label classification is to build a model $h : \chi \to 2^{|L|}$, which is used to predict the proper label set for a new instance.

ML.KNN [13] is one of the state-of-the-art algorithms in the multi-label learning literature. To infer the label set for a new instance (i.e., bug report) X_{new} , ML.KNN follows three steps:

the computation of membership counting scores, the computation of ML.KNN scores, and the assignment of labels. We describe each of these steps in the following subsections.

1) Membership Counting Score: ML.KNN first identifies the k-nearest neighbors $knn(X_{new})$ of the new instance X_{new} from the training dataset. For each label l in the label set L, we count the number of instances assigned to label l in $knn(X_{new})$. Formally, we denote membership counting score $C_{X_{new}}(l)$ as the number of instances assigned to label l, i.e.,

$$C_{X_{new}}(l) = \sum_{b' \in knn(X_{new})} Y_{b'}(l), l \in L.$$

$$\tag{1}$$

2) ML.KNN Score: With the membership counting score $C_{X_{new}}(l)$ for each label l, we consider two events: H_1^l is the event that X_{new} is assigned to l, and H_0^l is the event X_{new} is not assigned to l. Moreover, E_m^l denotes the event that there are exactly m instances that are assigned to label l, among the k nearest neighbors of X_{new} . Then, the ML.KNN score for l is the probability that the event X_{new} is assigned to l, given that exactly $C_{X_{new}}(l)$ instances are assigned to label l, i.e.,

$$ML.KNN_{X_{new}}(l) = P\left(H_1^l | E_{C_{X_{new}}(l)}^l\right).$$
(2)

From (2) and using the Bayes rule, we can derive

$$ML.KNN_{X_{new}}(l) = \frac{P\left(H_{1}^{l}\right) \times P\left(E_{C_{X_{new}}(l)}^{l}|H_{1}^{l}\right)}{\sum_{i \in \{0,1\}} P\left(H_{i}^{l}\right) \times P\left(E_{C_{X_{new}}(l)}^{l}|H_{i}^{l}\right)}.$$
(3)

The parameters of $P(H_1^l)$, $P(H_1^0)$, $P(E_m^l|H_1^l)$, and $P(E_m^0|H_1^0)$ can be inferred from the training dataset. The details of the inference process is available in [13].

3) Label Assignment: After the ML.KNN score for each label *l* is obtained, to decide whether a label should be assigned to X_{new} , ML.KNN uses the following heuristics: if $P(H_1^l) \times P(E_{C_{X_{new}}(l)}^l | H_1^l) > P(H_1^0) \times P(E_{C_{X_{new}}(l)}^l | H_1^0)$, then *l* is assigned to X_{new} .

III. OVERALL FRAMEWORK

Fig. 2 shows the overall framework of *Im-ML.KNN*. The framework includes two phases: the model building phase and the prediction phase. In the model building phase, our goal is to build a composite model *MLComposer*, from historical bug reports, which have known bug report field reassignment and refinement information. In the prediction phase, this classifier is used to predict the fields that will get reassigned and refined for a new bug report.

Our framework first extracts features from the set of training bug reports (i.e., bug reports with known field reassignments and refinements) (Step 1). Features are various quantifiable characteristics of bug reports that could potentially differentiate reports for different fields reassignment. In this paper, we consider two types of features: meta features and textual features.³ Next, we analyze the history of the training bug reports, and extract the field reassignment and refinement information (Step 2). Each field corresponds to a label, and in total we have eight

³For more details, please refer to Section IV-A.



N

Fig. 2. Overall framework of Im-ML.KNN.

labels which corresponds to eight types of bug report field reassignments and refinements (i.e., product, component, severity, priority, OS, version, fixer, and status reassignment).⁴ The training set is constructed after the feature and label extraction.

Next, our framework constructs three multilabel classifiers based on labels and different features of the training set (Step 3). In this paper, we use ML.KNN [13] to construct the three multilabel classifiers. The meta multi-label classifier is built based on the meta features of bug reports. The text multi-label classifier is built based on the textual features of bug reports. The mixed multilabel classifier is built based on the two types (i.e., meta features and textual features) of features of bug reports. A multilabel classifier is a machine learning model, which assigns a set of labels (in our case: bug report fields that would get reassigned and refined) to a data point (in our case: a bug report) based on its features. We then combine the three classifiers together to construct a *MLComposer* classifier (Step 4).

After *MLComposer* is constructed, it is used in the prediction phase to predict the fields that will get reassigned and refined in a new bug report. For each such bug report, we first extract features from it as we do in the model building phase (Step 4). Then, we input the features to *MLComposer* (Step 5). This step outputs the prediction results, which is a set of labels corresponding to the bug report fields that get reassigned and refined.

IV. FEATURE AND LABEL EXTRACTION

Here, we first describe the features we extracted from bug reports in Section IV-A. Next, we present the way we extract the labels from the training bug reports in Section IV-B.

A. Feature Extraction

A bug report contains a large amount of useful information, such as its textual description, and the values of its many fields. To predict which bug fields will be reassigned and refined, we extract many features from bug reports. We divide them into two categories: meta features and textual features.

1) Meta Features: Meta features refer to the non-textual fields of a bug report, e.g., reporter, assignee, product, and component. These fields are important for bug triaging and fixing [2], [3], [16]. Table I presents the meta features which are used

| | | Т | ABLE I | | |
|---------|-----------|--------|-----------------|-------|--------------|
| IETA FI | EATURES F | OR BUG | G REPORT | FIELD | REASSIGNMENT |

| Features | Description | Example |
|-----------|---------------------------------------|-------------|
| Reporter | The developer who reports the bug. | d_a_carver |
| Assignee | The assignee before this field is | wtp.inc- |
| | reassigned and refined. | inbox |
| Product | The product before this field is re- | WTP Incuba- |
| | assigned and refined. | tor |
| Component | The component before this field is | incubator |
| | reassigned and refined. | |
| Severity | The severity before this field is re- | normal |
| | assigned and refined. | |
| Priority | The priority before this field is re- | p3 |
| | assigned and refined. | |
| OS | The OS before this field is reas- | All |
| | signed and refined. | |
| Version | The product before this field is re- | unspecified |
| | assigned and refined. | |
| Platform | The platform before this field is | PC |
| | reassigned and refined. | |

to predict which bug fields get reassigned and refined. We extract 9 fields, and we record the values of these fields when a bug is reported—before any reassignments and refinements (if any). Notice that the value of the reporter field is unchanged for the whole life cycle of a bug report—there is no reassignment and refinement for this field. In Table I, column **Example** corresponds to the values of the fields of the example bug report shown in Fig. 1. This bug report has product, component, fixer, and status reassignments and refinements, so we trace the mixed values of these four fields from its bug history. For the other fields, we use the values recorded in the final bug report.

2) Textual Features: We extract the text in the summary and description fields, and then we tokenize them, remove the stop words, stem them (i.e., reduce them to their root form, e.g., write and written are reduced to writ) using the Porter stemmer, and represent them as TD-IDF (i.e., term frequency.inverse document frequency) vectors [17]. Formally, we represent terms in the *i*th bug report as a vector of term weights denoted by $b_i = \langle w_{i,1}, w_{i,2} \dots w_{i,v} \rangle$. The weight $w_{i,j}$ denotes the TD-IDF score [17] for the *j*th term in the *i*th bug report, which is computed as follows:

$$w_{i,j} = \frac{tf_{i,j}}{\text{Num of Terms in } b_i} \log\left(\frac{\text{Num of BugReports}}{\text{df}_j}\right)$$
(4)

where b_i denotes the *i*th bug report in the bug report collection, $tf_{i,j}$ denotes the term frequency of the *j*th term in the *i*th bug report, df_i denotes the document frequency of the *j*th term. Term frequency $tf_{i,j}$ refers to the number of times the *j*th term appears in the *i*th bug report. The document frequency of the *j*th term refers to the number of bug reports in which the *j*th term appears in. To reduce noise, we remove terms which appear less than ten times in the bug report collection.

B. Label Extraction

For the training bug reports, we need to extract the field reassignment and refinement information from the bug report history. Each field corresponds to a label, and in this paper, we consider eight types of bug report field reassignments and refinements considered in our previous study [9], i.e., component, product, severity, priority, OS, version, fixer, and status reassignment and refinement. For each of the training bug reports, we parse its history, and check whether any of its 8 fields got reassigned and refined. If a field was reassigned and refined, we set the corresponding label of the field to be "1"; otherwise "0". For example, in Fig. 1, we notice its product, component, fixer, and status fields get reassigned and refined. Thus, we set the corresponding labels of product, component, fixer, and status to be "1", and the remaining labels to be "0".

V. MLCOMPOSER: A COMPOSITE METHOD

ML.KNN is used to construct a multilabel classifier to predict the fields which would get reassigned and refined for bug reports. However, as we noted, for each type of field reassignment and refinement (except for the fixer reassignment), the number of bug reports whose fields have been reassigned and refined is much smaller than the number of bug reports without reassignment, i.e., the class imbalance phenomenon [14] is observed. For example, in Eclipse, only 9.76%, 18.44%, 9.19%, and 8.14% of bug reports have their product, component, severity and status fields reassigned and refined; in Mozilla, only 19.27%, 24.68%, 7.23%, and 11.39% of bug reports have their product, component, severity and status fields reassigned and refined [9]. To adapt ML.KNN to work well in imbalanced multi-label data (i.e., having much less bug reports with reassigned and refined fields than bugs without reassigned and refined fields), and also considering that we have multiple types of features, i.e., meta features and textual features, in this section, we propose MLComposer which combines three multilabel classifiers (ML.KNN classifiers) built on different types of features and considers the imbalance phenomenon. In this section, we first define three sets of scores outputted by the three classifiers. Next, we describe how we combine these scores together to construct the MLComposer classifier.

A. Feature Scores

As illustrated in Fig. 2, our proposed framework has three different multi-label classifiers (i.e., ML.KNN classifiers built using each of the three feature types). Let us refer to them as ML.KNN_{Meta}, ML.KNN_{Text}, and ML.KNN_{Mixed}. Given an unknown bug report, ML.KNN_{Meta}, ML.KNN_{Text}, and ML.KNN_{Mixed} output the following meta scores, text scores, and mixed scores, respectively:

Definition 1: (Meta Scores.) Consider a set of training bug reports BR, its corresponding set of meta feature values Meta, and its corresponding set of labels L. We build a ML.KNN classifier ML.KNN_{Meta} trained on Meta. For a new bug report br, for each label $l \in L$, we use ML.KNN_{Meta} to get the likelihood that br will be assigned to the label l (i.e., the field corresponds to label l would get reassigned and refined). We refer to the likelihood score as the **meta score** for label l, and denote it as ML.KNN_{Meta}(br, l).

Definition 2: (Text Scores.) Consider a set of training bug reports BR, its corresponding set of text feature values Text, and its corresponding set of labels L. We build a ML.KNN classifier ML.KNN_{Text} trained on Text. For a new bug report br, for each label $l \in L$, we use ML.KNN_{Text} to get the likelihood that br will be assigned to the label l. We refer to the likelihood score as the text score for label l, and denote it as ML.KNN_{Text} (br, l).

Definition 3: (Mixed Scores.) Consider a set of training bug reports BR, its corresponding set of meta and text feature values Mixed, and its corresponding set of labels L. We build a ML.KNN classifier ML.KNN_{Mixed} trained on Mixed. For a new bug report br, for each label $l \in L$, we use ML.KNN_{Mixed} to get the likelihood that br will be assigned to the label l. We refer to the likelihood score as the **mixed score** for label l and denote it as ML.KNN_{Text}(br, l).

B. MLComposer

Here, we propose *MLComposer*, a composite method which uses all of these three scores and considers the imbalance phenomenon in bug report field reassignments and refinements. A linear combination of meta scores, text scores, and mixed scores is used to compute the final *MLComposer* scores.

Definition 4: (MLComposer Score.) Consider a training bug report collection BR, and its corresponding multi-label classifiers for meta, description, and mixed features (ML.KNN_{Meta}, ML.KNN_{Text}, and ML.KNN_{Mixed}), respectively. For a new bug report br, for each label $l \in L$ we compute its corresponding meta, text and mixed scores, then its MLComposer score, denoted as MLComposer(br, l), which is a linear combination of the three scores, is defined as follows:

$$\begin{aligned} \text{MLComposer}(br, l) = & \alpha \times \text{ML.KNN}_{\text{meta}}(br, l) + \beta \\ & \times \text{ML.KNN}_{\text{text}}(br, l) \\ & + \gamma \times \text{ML.KNN}_{\text{mixed}}(br, l). \end{aligned}$$
(5)

In the above equations, $\alpha \in [0,1]$, $\beta \in [0,1]$, and $\gamma \in [0,1]$, and $\alpha + \beta + \gamma = 1$.

To deal with imbalanced data, *MLComposer* introduces a threshold for every label. Each threshold is independently fine tuned based on a sample of a training data so that the bias introduced by the imbalanced data can be offset. For each label $l \in L$, we define a threshold hreshold_l. To decide whether a label l is assigned to a new bug report (aka an instance) br, we follow the following equation:

$$\text{Label}_{br}(l) = \begin{cases} 1, & \text{if } \text{MLComposer}(br, l) \geq \text{threshold}_l \\ 0, & \text{otherwise.} \end{cases}$$
(6)

The value of threshold $_l$ for each label l can be trained from the training bug report collection. To automatically produce

good α , β , γ , and threshold_l ($l \in L$) values for *MLComposer*, we propose a greedy algorithm.

Fig. 1 presents the detailed steps to estimate good α , β , γ , and threshold values. We input a bug report collection BR, label set L (i.e., various types of bug report field reassignment), sample size Sample, meta features Meta, textual features Text, mixed features Mixed, and the number of neighbors K. We first sample a small bug report collection Samp_{BR} according to the sample size Sample (Line 12). Next, we initialize α , β , γ , and threshold_l ($l \in L$) values to 0 at Line 13. Then, we build the classifiers (i.e., $ML.KNN_{Meta}$, $ML.KNN_{Text}$, and ML.KNN_{Mixed}) for meta features, textual features, and mixed features using BR, and compute their corresponding meta, text, and mixed scores of bug reports in Samp_{BR} at Lines 14, 15, and 16, respectively. Next, we incrementally increase α , β , γ , and threshold values (Lines 17 to 21). We increase α from 0 to 1, and beta from 0 to $(1 - \alpha)$, in 0.1 increments. The value of γ is set as $(1 - \alpha - \beta)$. We increase the threshold_l for each label l in L from 0 to 1, in 0.01 increments. We use a finer granularity step to tune threshold l since it directly decides whether a bug report will be assigned to label l. We use a coarser granularity step to tune α , β , and γ values to reduce the computational cost in the tuning process. For each configuration of α , β , γ , and threshold, values, we build a composite model and compute the resultant F-measure score using bug reports in SampBR (Lines 20 to 26). Finally, Algorithm 1 returns α , β , γ , and threshold_l values resulting in the best average F-measure scores across all the labels l in L (Line 32).

Algorithm 1 Estimation of Good α , β , γ , and threshold_l ($l \in L$) values in *MLComposer*.

1: Estimatevalue(BR, L, Sample, Meta, Text, Mixed, K)

2: Input:

- 3: BR: Training bug report collection and their labels
- 4: L: Label set
- 5: Sample: Sample size (default value: 10% of |BR|)
- 6: Meta: Meta features
- 7: Text: Textual features
- 8: Mixed: Mixed features
- 9: K: Number of neighbors for ML.KNN

```
10: Output: \alpha, \beta, \gamma, and threshold<sub>l</sub> (l \in L)
```

11: Method:

12: Sample a bug report collection $Samp_{BR}$ of size Sample from BR;

13: $\alpha = 0, \beta = 0, \gamma = 0$, threshold_l = 0 ($l \in L$);

14: Build ML.KNN_{Meta} for Meta and BR, compute meta scores for each bug report in Samp_{BR};

15: Build ML.KNN $_{Text}$ for Text and BR, compute text scores for each bug report in Samp_{BR};

16: Build ML.KNN_{Mixed} for Mixed and BR, compute mixed scores for each bug report in $Samp_{BR}$;

17: for all α from 0 to 1, every time increase α by 0.1 do

18: for all β from 0 to $(1 - \alpha)$, every time increase β by 0.1 do

19: $\gamma = 1 - \alpha - \beta;$

20: for all labels $l \in L$ do

21: for all threshold l from 0 to 1, every time increase threshold by 0.01 do

22: for all Bug report br in Samp_{BR} do

23: Compute *MLComposer* score according to Definition 4;

24: Decide whether br is assigned to label l using Equation (6);

25: end for

26: Compute the F-measure score of the *l*th label;

- 27: end for
- 28: end for

29: Compute the average F-measure score across all the labels in L.

- 30: end for
- 31: end for

32: **Return** α , β , γ , and threshold_l ($l \in L$), which maximize average F-measure score across all of the labels in L.

VI. EXPERIMENTS AND RESULTS

In this section, we evaluate *Im-ML.KNN*. The experimental environment is a Windows 7, 64-bit, Intel(R) Xeon(R) 2.53 GHz server with 24 GB RAM. We first present our experiment setup and 6 research questions. We then present our experiment results that answer each of the 6 research questions.

A. Experiment Setup

Table II shows the statistics of the four projects we use to evaluate the performance *Im-ML.KNN* which are also used in our previous empirical study [9]. All of the bug reports and data are downloaded from their corresponding bug tracking systems. We collect all bug reports with the status "resolved", "closed", and "fixed" following previous studies [5]–[7], [12], [18]. In Table II, columns **Time** and **# Report** correspond to the time periods the collected bug reports are reported and the number of collected reports, respectively. In total, we collect 190 558 bug reports. Columns **# reporter**, **# fixer**, **# product**, **# component**, **# version**, **# OS**, and **# platform** correspond to the number of unique values of the different fields. Notice that the values of these fields are recorded at the time the bug report is submitted, i.e., the values of all of these fields are recorded before the fields of the bug report are reassigned and refined.

| Project | Time | # Reports | # Reporter | # Fixer | # Product | # Component | # Version | # OS | # Platform |
|------------|-------------------------|-----------|------------|---------|-----------|-------------|-----------|------|------------|
| OpenOffice | 2002-05-17 - 2013-04-07 | 42,169 | 5,451 | 701 | 140 | 106 | 546 | 45 | 12 |
| Netbeans | 2008-01-01 - 2013-03-13 | 46,345 | 5,709 | 323 | 112 | 684 | 43 | 26 | 7 |
| Eclipse | 2008-01-01 - 2011-07-19 | 50,639 | 5,824 | 1,021 | 143 | 702 | 220 | 31 | 6 |
| Mozilla | 2009-06-23 - 2012-02-23 | 51,405 | 3,536 | 696 | 51 | 620 | 107 | 36 | 10 |

TABLE II STATISTICS OF COLLECTED BUG REPORTS

We use ten times tenfold cross validation [19] to evaluate the performance of *Im-ML.KNN*. We randomly divide the dataset into ten folds. Of these ten folds, nine folds are used to train the model, while the remaining one fold is used to evaluate the performance. The whole process iterates ten times. The overall performance score across the ten iterations is reported. Also, we run tenfold cross validation ten times and record the average performance to further reduce the bias due to training set selection. Cross validation is a standard evaluation setting, which is widely used in software engineering studies, see [5], [20]–[24].

We implement *Im-ML.KNN* on top of Mulan [25], which is a multilabel learning Java toolkit. By default, we set the number of neighbors K = 10 as [13], and the sample size to 10% of the number of bug reports in the training dataset. For ML.KNN, we directly use its implementation in Mulan, and we set K = 10 which is the same as *Im-ML.KNN*.

Lamkanfi et al. propose the usage of Naive Bayes to predict whether a component field would be reassigned and refined [6]. The output of their method is only reassigned and refined or nonreassigned and refined for the component field of a bug report, which corresponds to the single-label learning problem in machine learning literature [26]–[28]. Different from their work, our works focus on predicting the sets of bug report fields which would get reassigned and refined, the output of our method is multiple labels which represents the fields of bug reports, which is a typical multi-label learning problem. To adapt Lamkanfi et al.'s method, we use their method to predict the reassignment and refinement of each field independently, and repeat the process 8 times. In this way, we build 8 classifiers using Naive Bayes, and each classifier predict one type of field reassignment. For example, classifier 1 could correspond to the classifier which predict whether the component field of a bug report would get reassigned and refined, classifier 2 could correspond to the classifier which predict whether the product field of a bug report would get reassigned and refined.

In multilabel learning literature, Tsoumakas *et al.* propose HOMER algorithm which also considers the class imbalance problem [15]. HOMER builds a hierarchy of multi-label classifiers by leveraging a balanced clustering algorithm, each one dealing with a much smaller set of labels compared to the total *L* labels, and a more balanced example distribution. Tsoumakas *et al.* use Naive Bayes as the underlying classifier of HOMER (referred to in this paper as HOMER-NB). In this paper, we also compare Im-ML.KNN with HOMER-NB.

B. Evaluation Metrics

To measure the performance of Im-ML.KNN, we use precision, recall, and F-measure scores as our evaluation metrics. We refer to this type of bug report field reassignment and refinement as a label l in multilabel learning literature. Give a label l in the label set L, for an instance (aka a bug report), there are four outcomes: an instance is assigned to the label l when it is truly assigned to l (true positive, TP_l); it assigned to label l when it is not actually assigned to l (false positive, FP_l); it is not assigned to label l when it is actually assigned to l (false negative, FN_l); or it is not assigned to label l when it actually is not assigned to l (true negative, TN_l). Based on these possible outcomes, we compute its own F-measure, precision, and recall, i.e., we have eight F-measures, precisions, and recalls, one for each label l:.

Precision for *l*: the proportion of bug reports (instances) that are correctly labeled as *l* among those labeled as *l*:

$$P_l = \frac{TP_l}{TP_l + FP_l}.$$
(7)

Recall for *l*: the proportion of bug reports labeled as *l* that are correctly labeled:

$$R_l = \frac{TP_l}{TP_l + FN_l}.$$
(8)

F-measure for l: a summary measure that combines both precision and recall for label l—it evaluates whether an increase in precision (recall) outweighs a reduction in recall (precision):

$$F_l = \frac{2 \times P_l \times R_l}{P_l + R_l}.$$
(9)

In addition to the eight precision, recall, and F-measure scores, we also compute in the average precision, recall, and F-measure scores over the eight precision, recall, and F-measure scores as

$$Ave.P = \frac{1}{|L|} \sum_{l \in L} P_l$$

$$Ave.R = \frac{1}{|L|} \sum_{l \in L} R_l$$

$$Ave.F = \frac{1}{|L|} \sum_{l \in L} F_l.$$
(10)

Notice that the average precision, recall, and F-measure measure the prediction performance across all of the |L| labels, which are also used in previous software engineering studies [20], [29], and many multilabel learning studies [26]–[28].

C. Research Questions

We would like to answer the following research questions.

- 1) What is the F-measure of *Im-ML.KNN*? How much improvement can it achieve over the method proposed by Lamkanfi *et al.* [6], ML.KNN [13], and HOMER-NB [15]?
- 2) Can the F-measure of Im-ML.KNN outperforms those of its constituent components (i.e., meta classifier, text classifier, and mixed classifier)?

TABLE III

EXPERIMENT RESULTS OF *Im-ML.KNN* COMPARED WITH THE METHOD PROPOSED BY LAMKANFI *ET AL.* [6]. WE CONSIDER MACRO-AVERAGE F-MEASURE (AVE. F-MEA.) AND THE F-MEASURE FOR EACH TYPE OF BUG REPORT FIELD REASSIGNMENT. Ave. = Average, Pro. = Product, Com. = Component, Sev. = Severity, Pri. = Priority, Ver. = Version, Fix. = Fixer, Stat. = Status

| Projects | Algorithms | Ave.F-mea | Comp.F-mea. | Pro.F-mea. | Sev.F-mea. | Pri.F-mea. | OS F-mea. | Ver.F-mea. | Fix.F-mea. | Stat.F-mea. |
|------------|-------------------|-----------|-------------|------------|------------|------------|-----------|------------|------------|-------------|
| | Im-ML.KNN | 0.6204 | 0.7284 | 0.7944 | 0.7551 | 0.2954 | 0.3583 | 0.6522 | 0.9056 | 0.4742 |
| OpenOffice | Lamkanfi el al.'s | 0.2731 | 0.2729 | 0.3044 | 0.0190 | 0.1993 | 0.1165 | 0.2122 | 0.6269 | 0.4335 |
| | Improvement. | 127.17% | 166.91% | 160.98% | 3874.08% | 48.22% | 207.51% | 207.37% | 44.46% | 0.38% |
| | Im-ML.KNN | 0.5963 | 0.9304 | 0.8693 | 0.0000 | 0.2856 | 0.5306 | 0.5821 | 0.7788 | 0.1971 |
| Netbeans | Lamkanfi el al.'s | 0.3007 | 0.5064 | 0.4952 | 0.0000 | 0.2792 | 0.0936 | 0.0936 | 0.4132 | 0.1918 |
| | Improvement. | 98.30% | 83.73% | 75.54% | 0.00% | 2.28% | 466.84% | 521.93% | 88.49% | 2.76% |
| | Im-ML.KNN | 0.5597 | 0.6365 | 0.7334 | 0.2577 | 0.5413 | 0.6606 | 0.6341 | 0.8667 | 0.1475 |
| Eclipse | Lamkanfi el al.'s | 0.2338 | 0.3190 | 0.1858 | 0.1758 | 0.2052 | 0.0904 | 0.2311 | 0.5123 | 0.1505 |
| | Improvement. | 139.39% | 99.54% | 294.74% | 46.60% | 163.77% | 630.80% | 174.36% | 69.19% | -2.01% |
| | Im-ML.KNN | 0.5796 | 0.7395 | 0.8123 | 0.2392 | 0.4817 | 0.7301 | 0.5843 | 0.8685 | 0.1813 |
| Mozilla | Lamkanfi el al.'s | 0.2710 | 0.4174 | 0.3380 | 0.1420 | 0.2206 | 0.2404 | 0.1907 | 0.4463 | 0.1724 |
| | Improvement. | 113.87% | 77.18% | 140.31% | 68.48% | 118.36% | 203.70% | 206.40% | 94.59% | 5.17% |

 TABLE IV

 EXPERIMENT RESULTS OF Im-ML.KNN COMPARED WITH ML.KNN [13]

| Projects | Algorithms | Ave.F-mea | Comp.F-mea. | Pro.F-mea. | Sev.F-mea. | Pri.F-mea. | OS F-mea. | Ver.F-mea. | Fix.F-mea. | Stat.F-mea. |
|------------|--------------|-----------|-------------|------------|------------|------------|-----------|------------|------------|-------------|
| | Im-ML.KNN | 0.6204 | 0.7284 | 0.7944 | 0.7551 | 0.2954 | 0.3583 | 0.6522 | 0.9056 | 0.4742 |
| OpenOffice | ML.KNN | 0.6144 | 0.8272 | 0.8652 | 0.7769 | 0.1075 | 0.2314 | 0.7058 | 0.9271 | 0.4739 |
| | Improvement. | 0.98% | -11.95% | -8.18% | -2.80% | 174.67% | 54.84% | -7.59% | -2.31% | 0.05% |
| | Im-ML.KNN | 0.5963 | 0.9304 | 0.8693 | 0.0000 | 0.2856 | 0.5306 | 0.5821 | 0.7788 | 0.1971 |
| Netbeans | ML.KNN | 0.5184 | 0.9407 | 0.8866 | 0.0000 | 0.0141 | 0.4729 | 0.5296 | 0.7845 | 0.0004 |
| | Improvement. | 15.03% | -1.10% | -1.95% | 0.00% | 1929.89% | 12.18% | 9.93% | -0.72% | 49175.00% |
| | Im-ML.KNN | 0.5597 | 0.6365 | 0.7334 | 0.2577 | 0.5413 | 0.6606 | 0.6341 | 0.8667 | 0.1475 |
| Eclipse | ML.KNN | 0.5095 | 0.6456 | 0.7523 | 0.0365 | 0.5274 | 0.6296 | 0.6147 | 0.8699 | 0.0000 |
| | Improvement. | 9.85% | -1.41% | -2.51% | 606.69% | 2.64% | 4.93% | 3.15% | -0.36% | ∞ |
| | Im-ML.KNN | 0.5796 | 0.7395 | 0.8123 | 0.2392 | 0.4817 | 0.7301 | 0.5843 | 0.8685 | 0.1813 |
| Mozilla | ML.KNN | 0.5242 | 0.7834 | 0.8554 | 0.0128 | 0.3221 | 0.7139 | 0.5979 | 0.8743 | 0.0340 |
| | Improvement. | 10.57% | -5.60% | -5.04% | 1770.54% | 49.55% | 2.27% | -2.27% | -0.67% | 433.80% |

 TABLE V

 EXPERIMENT RESULTS OF Im-ML.KNN COMPARED WITH HOMER-NB [15]

| Projects | Algorithms | Ave.F-mea | Comp.F-mea. | Pro.F-mea. | Sev.F-mea. | Pri.F-mea. | OS F-mea. | Ver.F-mea. | Fix.F-mea. | Stat.F-mea. |
|------------|--------------|-----------|-------------|------------|------------|------------|-----------|------------|------------|-------------|
| | Im-ML.KNN | 0.6204 | 0.7284 | 0.7944 | 0.7551 | 0.2954 | 0.3583 | 0.6522 | 0.9056 | 0.4742 |
| OpenOffice | HOMER-NB | 0.2342 | 0.3551 | 0.3130 | 0.0203 | 0.1850 | 0.1242 | 0.2554 | 0.2411 | 0.3803 |
| | Improvement. | 164.90% | 105.11% | 153.84% | 3621.76% | 59.70% | 188.58% | 155.35% | 275.69% | 24.69% |
| | Im-ML.KNN | 0.5963 | 0.9304 | 0.8693 | 0.0000 | 0.2856 | 0.5306 | 0.5821 | 0.7788 | 0.1971 |
| Netbeans | HOMER-NB | 0.2398 | 0.5099 | 0.3289 | 0.0000 | 0.1971 | 0.1171 | 0.1060 | 0.2291 | 0.1907 |
| | Improvement. | 148.67% | 82.46% | 164.28% | 0.00% | 44.89% | 353.12% | 449.02% | 239.96% | 3.36% |
| | Im-ML.KNN | 0.5597 | 0.6365 | 0.7334 | 0.2577 | 0.5413 | 0.6606 | 0.6341 | 0.8667 | 0.1475 |
| Eclipse | HOMER-NB | 0.1937 | 0.2891 | 0.2088 | 0.1557 | 0.2491 | 0.1040 | 0.1937 | 0.2031 | 0.1468 |
| | Improvement. | 188.95% | 120.16% | 251.25% | 65.55% | 117.33% | 535.32% | 227.35% | 326.75% | 0.48% |
| | Im-ML.KNN | 0.5796 | 0.7395 | 0.8123 | 0.2392 | 0.4817 | 0.7301 | 0.5843 | 0.8685 | 0.1813 |
| Mozilla | HOMER-NB | 0.2397 | 0.4050 | 0.3972 | 0.1446 | 0.2441 | 0.2252 | 0.2460 | 0.0950 | 0.1613 |
| | Improvement. | 141.80% | 82.58% | 104.53% | 65.48% | 97.37% | 224.19% | 137.55% | 814.01% | 12.40% |

- 3) Do different numbers of neighbors affect the F-measure of *Im-ML.KNN*?
- 4) What are good predictors for bug report field reassignments and refinements? Do the predictors differ for different fields?
- 5) What is the effect of varying the amount of training data on the effectiveness of *Im-ML.KNN*?
- 6) How much time does it take for Im-ML.KNN to run?

Answering question 1) sheds light on the effectiveness of *Im-ML.KNN* to predict bug report fields that get reassigned and refined, compared to existing state-of-the-art solutions [6], [13]. Answering question 2) highlights the effectiveness of our approach compared to each of its individual classifiers. Answering question 3) sheds light on the sensitivity of *Im-ML.KNN* when using various settings of its parameter, i.e., the number of neighbors. The answer of question 4) presents the top features that best indicate bug report field reassignments and refinements,

which can be used by software practitioners to determine, early on, which fields are most likely to be reassigned and refined. The answer to question 5) determines the impact of reducing the amount of training data on the performance of our approach. The answer to question 6) examines the model building time and prediction time for Im-ML.KNN.

D. RQ1: F-Measure Scores of Im-ML.KNN

Tables III–V present the experimental results of Im-ML.KNN compared with the method proposed by Lamkanfi *et al.* [6], ML.KNN [13], and HOMER-NB [15], respectively. We also list the average precision and recall of Im-ML.KNN, Lamkanfi *et al.*'s method, ML.KNN and HOMER-NB in Table VI. Notice that, for Netbeans, no bug report has its severity reassigned and refined, therefore the precision, recall, and F-measure for severity reassignment and refinement is 0.

TABLE VI AVERAGE PRECISION (AVE. PRECISION) AND RECALL (AVE. RECALL) OF IM-ML.KNN, LAMKANFI EL AL.'S METHOD, ML.KNN, AND HOMER-NB

| Project | Algorithms | Ave. Precision | Ave. Recall |
|------------|-------------------|----------------|-------------|
| | Im-ML.KNN | 0.6090 | 0.6406 |
| OpenOffice | Lamkanfi el al.'s | 0.2237 | 0.8379 |
| Openomice | ML.KNN | 0.8030 | 0.5491 |
| | HOMER-NB | 0.2711 | 0.4115 |
| | Im-ML.KNN | 0.6113 | 0.5914 |
| Netheans | Lamkanfi el al.'s | 0.2636 | 0.6010 |
| Netbeans | ML.KNN | 0.7352 | 0.4697 |
| | HOMER-NB | 0.3378 | 0.2996 |
| | Im-ML.KNN | 0.5671 | 0.5613 |
| Eclipse | Lamkanfi el al.'s | 0.1929 | 0.8154 |
| Lenpse | ML.KNN | 0.6923 | 0.4318 |
| | HOMER-NB | 0.2279 | 0.3788 |
| | Im-ML.KNN | 0.5739 | 0.5899 |
| Mozilla | Lamkanfi el al.'s | 0.2194 | 0.2194 |
| wiozilia | ML.KNN | 0.7776 | 0.4775 |
| | HOMER-NB | 0.2588 | 0.4664 |

Precision and recall are both important metrics for reassigned and refined bug prediction since they measure quality in two aspects. If the precision is low, then the developer would not use the technique, due to a high number of false alarms. On the other hand, if the recall is low, which means that most reassigned and refined bug reports are not successfully detected, developers would also not use the technique. There is a tradeoff between precision and recall [19]. One can increase precision by sacrificing recall (and *vice versa*). One simple way to increase recall is to predict all the bug reports as reassigned and refined, then the recall would be 1 but the precision would be 0. In our method, we can sacrifice precision (recall) to increase recall (precision), by manually lowering (increasing) the value of the $threshold_l$ parameter in (6). F-measure, which is a weighted harmonic mean of precision and recall, is often used to judge whether an increase in precision outweighs a loss in recall (and vice versa) [19]. Thus, in many existing papers, e.g., [22], [30]–[32], it is often used as a summary measure. In Fig. 1, the threshold parameter is automatically tuned to maximize the F-measure for each type of bug report field reassignment and refinementin the training data.

From Table III, we note that the improvement of our method over Lamkanfi *et al.*'s method is substantial. We improve the average F-measure of the method proposed by Lamkanfi *et al.* by 127.17%, 98.30%, 139.39%, and 113.87% for OpenOffice, Netbeans, Eclipse, and Mozilla, respectively. Averaging across the four datasets, the average improvement achieved by *Im-ML.KNN* is 119.69%.

From Table IV, the improvement of our method over ML.KNN is substantial. We improve the average F-measure of ML.KNN by 0.98%, 15.03%, 9.85%, and 10.57% for OpenOffice, Netbeans, Eclipse, and Mozilla, respectively. Averaging across the four datasets, the average improvement achieved by *Im-ML.KNN* is 9.11%. We also notice that ML.KNN does not work well for imbalanced data, for example, ML.KNN's F-measures for predicting status reassignment and refinementare quite low, i.e., 0.4739, 0.0004, 0.0000, and 0.0340 for OpenOffice, Netbeans, Eclipse, and Mozilla, respectively. Our method

TABLE VII Average F-measure of IM-ML.KNN Compared With Each of 3 Multi-Label Classifiers, i.e., Meta Classifier, Text Classifier, and Mixed Classifier

| Project | Im-ML.KNN | Data Type | ML.KNN | Improvement |
|------------|-----------|-----------|--------|-------------|
| | | Meta | 0.6197 | 0.11% |
| OpenOffice | 0.6204 | Text | 0.1972 | 214.60% |
| | | Mixed | 0.6144 | 0.98% |
| | | Meta | 0.5333 | 11.81% |
| Netbeans | 0.5963 | Text | 0.2691 | 121.59% |
| | | Mixed | 0.5184 | 15.03% |
| | | Meta | 0.5061 | 10.59% |
| Eclipse | 0.5597 | Text | 0.1977 | 183.11% |
| | | Mixed | 0.5095 | 9.85% |
| | | Meta | 0.5124 | 13.11% |
| Mozilla | 0.5796 | Text | 0.2436 | 137.93% |
| | | Mixed | 0.5242 | 10.57% |

TABLE VIII Average Weights for the Meta Classifier, Text Classifier, and Mixed Classifier

| Projects | Meta Classifier | Text Classifier | Mixed Classifier |
|------------|-----------------|-----------------|------------------|
| OpenOffice | 0.35 | 0.14 | 0.51 |
| Netbeans | 0.24 | 0.16 | 0.60 |
| Eclipse | 0.28 | 0.18 | 0.54 |
| Mozilla | 0.30 | 0.23 | 0.47 |

overcomes the weakness of ML.KNN and it can achieve better results for each type of bug report field reassignment.

From Table V, we note that the improvement of our method over HOMER-NB is substantial. We improve the average F-measure of HOMER-NB by 164.90%, 148.67%, 188.95%, and 141.80% for OpenOffice, Netbeans, Eclipse, and Mozilla, respectively. Averaging across the four datasets, the average improvement achieved by *Im-ML.KNN* is 161.08%. We also notice that HOMER-NB does not work well for OS reassignment, the F-measures for OS reassignment and refinementare quite low, i.e., 0.1242, 0.1171, 0.1040, and 0.2252 for for OpenOffice, Netbeans, Eclipse, and Mozilla, respectively. Notice the numbers of bug reports whose OS get reassigned and refined are quite small compared to other types of field reassignment and refinement—OS reassignment and refinementonly happens for 5.78%, 4.79%, 4.55%, and 12.34% of OpenOffice, Netbeans, Eclipse, and Mozilla bug reports respectively.

E. RQ2: Benefits of Composition

Table VII presents the average F-measure scores of Im-ML.KNN compared to the meta classifier, text classifier, and mixed classifier. We notice the improvement of Im-ML.KNN over the 3 classifiers are substantial. On average across the 4 projects, Im-ML.KNN improves the average F-measure scores of meta classifier, text classifier, and mixed classifier by 8.91%, 164.31%, and 9.11% respectively. The results show that it is beneficial to combine the 3 classifiers.

To investigate which classifier plays an important role in Im-ML.KNN, we presents the average weights of the meta classifier, text classifier, and mixed classifier in Table VIII. Note that we run tenfold cross validation ten times, and for each fold we have a set of weights. In total, we have 100 sets of weights, and we record the average weights across the 100 sets.

5 10 15 20 25 30 35 40 45 Number of Neighbors K Fig. 3. Experiment results of Im-ML.KNN for OpenOffice with number of neighbors K Varied from 5 to 45. Ave. = Average, Pro. =Product. Severity, Pri. Comp. Component, Sev. = = Priority., Ver. = Version, Stat. = Status

-- Pro.F-measure

Pri.F-measure

Fixer.F-measur

-_- Comp.F-measure

OS.F-measure

Stat.F-measure

-------*



Fig. 4. Experiment results of Im-ML.KNN for Netbeans with number of neighbors K Varied From 5 to 45.

From Table VIII, we observe that the mixed classifier plays the most important role in Im-ML.KNN, followed by meta classifier and text classifier.

F. RQ3: Sensitivity of Im-ML.KNN on Optimal Setting

Since the number of neighbors can impact the performance of the algorithm, we investigate the effect of varying the number of neighbors K on the performance of *Im-ML.KNN*. We vary the number of neighbors (i.e., K in Algorithm 1) from 5 to 45.

We plot the resultant F-measure scores for OpenOffice, Netbeans, Eclipse, and Mozilla in Fig. 3–6, respectively. For Openoffice, the average F-measure scores vary from 0.6073 (K= 5) to 0.6215 (K = 20). For Netbeans, the average F-measure scores vary from 0.5814 (K = 5) to 0.0.6007 (K = 20). For Eclipse, the average F-measure scores vary from 0.5540 (K = 45) to 0.5629 (K = 15). For Mozilla, the average F-measure scores vary from 0.5763 (K = 5) to 0.5860 (K= 15). The results show that the performance of *Im-ML.KNN* is relatively stable with various numbers of neighbors. Across



Fig. 5. Experiment results of Im-ML.KNN for Eclipse with number of neighbors K varied from 5 to 45.



Fig. 6. Experiment results of Im-ML.KNN for mozilla with number of neighbors K varied from 5 to 45.

the 4 projects, Im-ML.KNN achieves the best performance with the number of neighbors K set to 15 or 20.

G. Indicators of Bug Field Reassignment

From the bug reports, we extract thousands of features (i.e., meta features and textual features). To understand which features are important to classify field reassignment, we extract discriminative features from the thousands of features. We extract top-5 features per label based on their information gain scores [19].

Table IX presents the top ten most discriminative features. We notice that the meta features (e.g., product, component, assignee) make up most of the top ten features. Notice that we use the value of the meta features before they are reassigned and refined (i.e., the first values of these features). We find that the first/initial values of these features can be good indictors to predict which fields would get reassigned and refined. Among the 4 projects, *product, component, reporter*, and *assignee* are the 4 most important meta features related to various types of field reassignment. For example, to predict whether the product field would get reassigned and refined, the value of the meta feature *product* is a good indictor, since the initial value of the *product*

1

F-measure Scores .0

0

Ave.F-measure

Sev.F-measure

Ver.F-measure

| Projects | Product | Component | Severity | Priority | OS | Version | Fixer | Status |
|------------|-----------------|----------------|----------------|----------------|------------------|-----------------|-----------------|------------------|
| | Product | Product | Severiry | Reporter | Reporter | Product | Assignee | Product |
| | Reporter | Reporter | Version | Assignee | OS | Reporter | Reporter | Reporter |
| OpenOffice | Assigee | Assigee | Reporter | Priority | Assignee | Assignee | Product | Assignee |
| - <u>-</u> | Component | Component | Assignee | Version | Version | Version | Version | Component |
| | Version | Version | OS | Product | Product | Component | Component | Version |
| | chart | chart | Component | Component | Component | chart | <u> </u> | chart |
| | ac | ac | Product | OS | Platform | ac | docum | ac |
| | star | checkap | attachm | crash | docum | star | <u>Platform</u> | star |
| | checkap | star | <u>Platorm</u> | <u>Platorm</u> | writer) | checkap | http | checkap |
| | diction | OS | gbuild | docum | spreadsheet | sockes | distribut | diction |
| | Product | Component | null | Reporter | Reporter | Version | Assignee | Product |
| | Component | Severity | null | Component | OS | Reporter | Reporter | Component |
| Netbeans | Reporter | Reporter | null | Assignee | Component | Component | Component | Reporter |
| | Assignee | Product | null | Priority | Assignee | Assignee | Product | Assignee |
| | Severity | Assignee | null | Product | Product | Product | Version | Severity |
| | Version | Version | null | Version | Version | disgram | Severity | Version |
| | <u>OS</u> | <u>Plaform</u> | null | project | stacktrac | macksic | diagram | <u>OS</u> |
| | bpel | OS | null | <u>OS</u> | Severity | Platform | OS | bpel |
| | <u>Platform</u> | attachm | null | sunflow | environm | Priority | scenari | Platform [Value] |
| | client | sever | null | start | comment | layoutdesign | makeproj | client |
| | Assignee | Component | Reporter | Reporter | Reporter | Reporter | Assignee | Reporter |
| | Component | Assignee | Assignee | Assignee | Assignee | Assignee | Reporter | Assignee |
| Eclipse | Reporter | Reporter | Component | Component | Component | Component | Component | Component |
| | Product | Product | Product | Product | Platform | Product | Product | Product |
| | Version | Version | Version | Version | Product | Version | Version | Version |
| | consmo | cosmo | Severity | clon | <u>OS</u> | identif | <u>OS</u> | <u>OS</u> |
| | jsdt | step | mylyn | init | Version | cosmo | step | respons |
| | cmdb | reproduc | task | creat | descript | reproduc | descript | reassign |
| | wikitext | build | OS | tptp | coco | mozil | build | clon |
| | inform | inform | tptp | 05 | birt | geck | reproduc | atricl |
| | Component | Component | Reporter | Component | Reporter | Reporter | Assignee | Reporter |
| Marilla | Reporter | Reporter | Component | Reporter | \underline{OS} | Component | Reporter | Component |
| Mozilla | Product | Product | Assignee | Product | Component | Product | Component | Assignee |
| | Assignee | Assignee | Product | Assignee | Assignee | "agent" | Product | Product |
| | "pag" | "firefox" | <u>OS</u> | Version | Product | "identif" | Version | Version |
| | local | Version | Version | OS | geck | Version | OS | mim |
| | attach | thank | Severity | thank | identif | geck | transl | altern |
| | thank | html | agent | commis | agent | Assignee | patch | localecod |
| | text | local | reproduc | pleas | Platform | reproduc | repositor | plain |
| | fil | text | identif | min | Version | user | attach | iphon |

 TABLE IX

 TOP TEN DISCRIMINATIVE FEATURES BASED ON INFORMATION GAIN SCORES. THE META FEATURES ARE UNDERLINED

field maybe wrong, corresponds to a non-existent product, or is a default value that most likely would get changed later. Aside from these meta features, some textual features, corresponding to stemmed words that appear in bug reports, are also good indicators to various field reassignments and refinements. Note that, in Table IX, the set of top ten features for Netbeans corresponding to label Severity is empty; this is the case since none of the Netbeans bug reports has its severity field reassigned and refined.

To further investigate why the most discriminative features differs for different types of bug report field reassignment and refinement, we also perform a simple qualitative analysis. Notice that the fields in a bug report are related; some feature combinations are good indicators for the field reassignment and refinement. For example, the combinations of product, component are important indicators to find the suitable fixers during the bug triaging process [6]. For some product and component combinations, it is easy to find suitable fixers. For some other combinations, it might be hard to find suitable fixers, which results in bugs being "tossed" among multiple fixers. Thus, the combinations of the product and component fields can help to decide whether the fixer field would get reassigned. For example, in the collected dataset of OpenOffice, the combination of product ="Writer", and component ="code" appears 2308 times, and there are total of 1892 times that the fixer fields are reassigned under this combination. In the collected dataset of Mozilla, the combination of product ="mozilla.org" and component ="Server Operations" appears 3,066 times, and there are a total of 2,914 times where the fixer fields are reassigned under this combination.

The feature combinations are also good indicators for other types of field reassignment and refinement. For example, in Netbeans, we notice that certain combinations of reporter, component, and assignee are good indicators for priority refinement. In the collected dataset of Netbeans, the combination of reporter ="soldatov", component ="code", and assignee ="issue" appear 166 times, and there is a total of 120 times that the priority fields are reassigned under this combination

To simulate the decision process of an experienced bug triager who needs to decide what bug report fields will get reassigned and refined, we create a baseline approach that infers reassigned and refined fields based on the statistics of

| Projects | Algorithms | Ave.F-mea | Comp.F-mea. | Pro.F-mea. | Sev.F-mea. | Pri.F-mea. | OS F-mea. | Ver.F-mea. | Fix.F-mea. | Stat.F-mea. |
|------------|--------------|-----------|-------------|------------|------------|------------|-----------|------------|------------|-------------|
| | Im-ML.KNN | 0.6204 | 0.7284 | 0.7944 | 0.7551 | 0.2954 | 0.3583 | 0.6522 | 0.9056 | 0.4742 |
| OpenOffice | Baseline | 0.5781 | 0.6913 | 0.7756 | 0.8848 | 0.1140 | 0.1001 | 0.6863 | 0.8553 | 0.5374 |
| | Improvement. | 7.32% | 5.37% | 2.43% | -12.68% | 159.20% | 257.82% | -4.97% | 5.88% | -11.76% |
| | Im-ML.KNN | 0.5963 | 0.9304 | 0.8693 | 0.0000 | 0.2856 | 0.5306 | 0.5821 | 0.7788 | 0.1971 |
| Netbeans | Baseline | 0.4633 | 0.7878 | 0.7208 | 0.0000 | 0.0970 | 0.0852 | 0.8223 | 0.6840 | 0.0460 |
| | Improvement. | 28.71% | 18.09% | 20.60% | 0.00% | 194.53% | 522.87% | -29.21% | 13.86% | 328.54% |
| | Im-ML.KNN | 0.5597 | 0.6365 | 0.7334 | 0.2577 | 0.5413 | 0.6606 | 0.6341 | 0.8667 | 0.1475 |
| Eclipse | Baseline | 0.4310 | 0.5992 | 0.6862 | 0.0760 | 0.4890 | 0.2175 | 0.5459 | 0.7866 | 0.0438 |
| | Improvement. | 29.87% | 6.23% | 6.88% | 239.28% | 10.69% | 203.68% | 15.37% | 10.19% | 236.74% |
| | Im-ML.KNN | 0.5796 | 0.7395 | 0.8123 | 0.2392 | 0.4817 | 0.7301 | 0.5843 | 0.8685 | 0.1813 |
| Mozilla | Baseline | 0.3837 | 0.6585 | 0.6776 | 0.0461 | 0.2631 | 0.2169 | 0.3875 | 0.7989 | 0.0211 |
| | Improvement. | 51.06% | 12.31% | 19.88% | 419.14% | 83.08% | 236.68% | 50.80% | 8.71% | 760.84% |

 TABLE X

 EXPERIMENT RESULTS OF Im-ML.KNN COMPARED WITH THE BASELINE APPROACH

the top ten discriminative features for each field reassignment and refinement. Since there are two types of features, i.e., meta features and textual features, we compute the statistics for these two types of features in different ways.

For a meta feature m, the baseline approach computes the probability for a field f to be reassigned and refined as follows: given a value v of the meta feature m, suppose the number of times v appears in the training bug reports is denoted as total, and the number of times v appears in the training bug reports whose field f get reassigned and refined is denoted as reassign, the probability that field f of a bug report with value v of meta feature f, to get reassigned, which is denoted by $\text{prob}_{f,t}$, and is computed by reassign/total.

For a textual feature t, and for a field f, we compute the number of bug reports in the training data whose field f is reassigned or refined (denoted as $total_f$), and also the number of bug reports in the training data whose field f is reassigned or refined and contains term t (denoted as $\operatorname{reassign}_{f,t}$). Based on the these numbers, we compute the probability for f to be reassigned given textual feature t, which is denoted as $\operatorname{prob}_{f,t}$, by taking the ratio of $\operatorname{reassign}_{f,t}$ and total_{f} .

To predict whether a field f will get reassigned and refined in a new bug report, the baseline approach first computes a probability for each of the top-10 discriminative features, considering the values of these features in the new bug report. If one of the probabilities is larger than or equal to 0.5, the baseline approach predicts that field f will get reassigned and refined; else it predicts that f will not be reassigned or refined.

Table X presents the F-measure scores of Im-ML.KNN compared with the baseline approach. We improve the average F-measure of the baseline approach by 7.32%, 28.71%, 29.87%, and 51.06% for OpenOffice, Netbeans, Eclipse, and Mozilla, respectively. Averaging across the four datasets, the average improvement achieved by Im-ML.KNN is 29.24%.

H. Varying the Amount of Training Data

In the previous research questions, we use tenfold cross validation, which means that 90% of the bug reports are used as training data. In this research questions, we would like to investigate the impact of reducing the amount of training data on the evaluation of our approach. In K-fold cross validation, ((k - 1)/k) * 100% of the data is used to train a model, and the remaining (1/k) * 100% of the data is used to test the model. K-fold cross validation is a standard approach. To answer this



Fig. 7. Average F-measure of Im-ML.KNN for OpenOffice, Netbeans, Eclipse, and Mozilla with various amount of training bug reports.

research question, we try to reduce the number of folds to reduce the amount of training data. We vary the number of K from 2 to 10, and for each value of K, we perform ten times K-fold cross-validation, and record the average F-measure scores.

Fig. 7 presents the average F-measure scores of Im-ML.KNN for OpenOffice, Netbeans, Eclipse, and Mozilla with various amount of training bug reports. The average F-measure scores vary from 0.4541-0.6226, 0.5624-0.5963, 0.5296-0.5683, and 0.5652-0.5956, for OpenOffice, Netbeans, Eclipse, and Mozilla, respectively. When we vary K from 10 to 2, the F-measure for Eclipse, Mozilla, and Firefox remains relatively stable (it fluctuates less than 5.68% of the original value). For OpenOffice, the F-measure reduces by 26.81% when we vary K from 10 to 2.

I. Time Efficiency of Im-ML.KNN

The time efficiency of Im-ML.KNN may affect its usability, therefore, we also investigate Im-ML.KNN's time efficiency. In this question, we investigate whether the runtime of Im-ML.KNN is reasonable. To answer this research question, we investigate the average amount of time that is needed by Im-ML.KNN and the baseline approaches to process a bug report during the model building phase, and the average amount of time it needs to predict the fields which would get reassigned and refined for a new bug report during the prediction phase. We use a Windows 7, 64-bit, Intel(R) Xeon(R) 2.53 GHz server with 24 GB RAM.

TABLE XI AVERAGE MODEL BUILDING TIME, AND PREDICTION TIME, PER BUG REPORT, FOR IM-ML.KNN, LAMKANFI EL AL.'S APPROACH, ML.KNN, AND HOMER-NB (IN SECONDS)

| Projects | Model Building Time | | | | Predictio | n | | |
|------------|---------------------|-------------------|--------|----------|-----------|-------------------|--------|----------|
| Trojects | Im.ML-KNN | Lamkanfi el al.'s | ML.KNN | HOMER-NB | Im.ML-KNN | Lamkanfi el al.'s | ML.KNN | HOMER-NB |
| OpenOffice | 0.0270 | 0.0333 | 0.0043 | 0.0299 | 0.0136 | 0.0330 | 0.0045 | 0.0317 |
| Netbeans | 0.0263 | 0.0348 | 0.0046 | 0.0391 | 0.0153 | 0.0344 | 0.0046 | 0.0296 |
| Eclipse | 0.0291 | 0.0443 | 0.0059 | 0.0382 | 0.0182 | 0.0435 | 0.0061 | 0.0389 |
| Mozilla | 0.0234 | 0.0384 | 0.0050 | 0.0346 | 0.0162 | 0.0420 | 0.0053 | 0.0348 |
| Average. | 0.0265 | 0.0377 | 0.0050 | 0.0355 | 0.0158 | 0.0382 | 0.0051 | 0.0338 |

Table XI shows the average model building time and prediction time per bug report for Im-ML.KNN, Lamkanfi et al.'s approach, ML.KNN, and HOMER-NB. We notice that the average model building time and the average prediction time of Im-ML.KNN are 0.0265 and 0.0158 s per bug report, respectively. Comparing with the other 3 baseline approaches, the average model building time and the average prediction time of Im-ML.KNN are better than those of Lamkanfi et al.'s approach and HOMER-NB, and worse than those of ML.KNN. Still, the time taken by Im-ML.KNN is reasonable. Note that the model building phase can be done offline (e.g., overnight). Also, a learned model can be used to predict reassigned and refined fields of many new bug reports, it is normal to spend a few hours to process hundreds of thousands of bug reports to initially build a model, since the model can be reused and the process can be done offline.

VII. DISCUSSION

A. Longitudinal Data Setup

To investigate whether Im-ML.KNN can be used to solve the problem in the same setting as the one in practice, we performed an experiment using a longitudinal data setup following Tamrawi *et al.* and Bhattacharya and Neamtiu [18], [33]. We sorted the bug reports in the order they are received (i.e., temporally) and split them into 11 nonoverlapping time windows of equal sizes, numbered 0 to 10. The process then proceeds as follows: First, in fold 1, we train using bug reports in window 0, and test the trained model using the bug reports in window 1. Then, in fold 2, we train using bug reports in window 1, and test the trained model using the bug reports in window 2, and so on. We proceed in a similar manner for the next folds. In the final fold (i.e., fold 10), we train using bug reports in window 9, and test using the bug reports in window 10. We record the average performance across the ten folds.

Table XII presents the average F-measure of Im-ML.KNN compared with Lamkanfi *et al.*'s, ML.KNN, and HOMER-NB. The average F-measure of *Im-ML.KNN* are 0.4187, 0.4848, 0.4154, and 0.4708 for OpenOffice, Netbeans, Eclipse, and Mozilla, respectively. The improvement of our method over Lamkanfi *et al.*'s method is substantial. We improve the average F-measure of the method proposed by Lamkanfi *et al.* by 54.20%, 53.17%, 73.87%, and 61.57% for OpenOffice, Netbeans, Eclipse, and Mozilla, respectively. Averaging across the four datasets, the average improvement achieved by *Im-ML.KNN* is 60.70%.

The improvement of our method over the ML.KNN method is substantial for Netbeans, Eclipse, and Mozilla. We improve

| IADLE AII |
|-----------|
|-----------|

AVERAGE F-MEASURE OF IM-ML.KNN COMPARED WITH LAMKANFI EL AL.'S, ML.KNN, AND HOMER-NB USING A LONGITUDINAL DATA SETUP. THE LAST ROW SHOW THE AVERAGE PERFORMANCE ACROSS THE 4 PROJECTS

| Projects | Im-ML.KNN | Lamkanfi el al.'s | Improvement. |
|------------|-----------|-------------------|--------------|
| OpenOffice | 0.4187 | 0.2715 | 54.20% |
| Netbeans | 0.4848 | 0.3165 | 53.17% |
| Eclipse | 0.4154 | 0.2389 | 73.87% |
| Mozilla | 0.4708 | 0.2914 | 61.57% |
| Average. | 0.4474 | 0.2796 | 60.70% |
| Projects | Im-ML.KNN | ML.KNN | Improvement. |
| OpenOffice | 0.4187 | 0.3925 | 6.68% |
| Netbeans | 0.4848 | 0.3865 | 25.43% |
| Eclipse | 0.4154 | 0.3543 | 17.25% |
| Mozilla | 0.4708 | 0.4237 | 11.12% |
| Average. | 0.4474 | 0.3892 | 15.12% |
| Projects | Im-ML.KNN | HOMER-NB | Improvement. |
| OpenOffice | 0.4187 | 0.2554 | 63.94% |
| Netbeans | 0.4848 | 0.2836 | 70.90% |
| Eclipse | 0.4154 | 0.2218 | 87.31% |
| Mozilla | 0.4708 | 0.2761 | 70.56% |
| Average. | 0.4474 | 0.2592 | 73.18% |

the average F-measure of ML.KNN by 6.68%, 25.43%, and 17.25%, and 11.12% for OpenOffice, Netbeans, Eclipse, and Mozilla, respectively. Averaging across the four datasets, the average improvement achieved by *Im-ML.KNN* is 15.12%.

The improvement of our method over the HOMER-NB method is substantial for Netbeans, Eclipse, and Mozilla. We improve the average F-measure of HOMER-NB by 63.94%, 70.90%, 87.31%, and 70.56% for OpenOffice, Netbeans, Eclipse, and Mozilla, respectively. Averaging across the four datasets, the average improvement achieved by *Im-ML.KNN* is 73.18%.

Fig. 8–11 present the average F-measure scores of Im-ML. KNN, Lamkanfi *et al.*'s approach, ML.KNN, and HOMER-NB for OpenOffice, Netbeans, Eclipse, and Mozilla, respectively. We note that the average F-measure scores of Im-ML.KNN outperform those of other approaches for most folds for the majority of the projects. Also, in OpenOffice, we notice there is a remarkable drop on Folds 8 and 9 for Im-ML.KNN, we double check the results, and it is the case.

B. Cost Analysis

Here, we analyze the cost of Im.ML-KNN. For a field f, if we correctly predict that the field will get reassigned and refined, let us assume that the time saved for bug fixing is s_f ; else if we wrongly predict that the field would get reassigned and refined,



Fig. 8. Experiment results of Im-ML.KNN, Lamkanfi *et al.*'s approach, ML.KNN, and HOMER-NB for OpenOffice with different folds.



Fig. 9. Experiment results of Im-ML.KNN, Lamkanfi *et al.*'s approach, ML.KNN, and HOMER-NB for netbeans with different folds.



Fig. 10. Experiment results of Im-ML.KNN, Lamkanfi *et al.*'s approach, ML.KNN, and HOMER-NB for Eclipse with different folds.

we assume that the extra time needed for bug fixing is w_f . Suppose we have n bug reports, and among the n bug reports, we correctly predict whether field f would get reassigned in m bug reports and incorrectly predict whether f would get reassigned in k bug reports, then the cost for Im-ML.KNN is $(m \times s_f) - (k$



Fig. 11. Experiment results of Im-ML.KNN, Lamkanfi *et al.*'s approach, ML.KNN, and HOMER-NB for Mozilla with different folds.

 $(\times w_f)$. If $(k \times w_f) \leq (m \times s_f)$, then our approach could help developers save time.

Table XIII presents the cost of Im-ML.KNN. We denote the time saved due to the correct prediction of component, product, severity, priority, os, version, fixer, and status reassignments and refinements as s_c , s_p , s_s , s_{pri} , s_o , s_v , s_f , and s_{st} , and the time wasted due to wrong prediction as $w_c, w_p, w_s, w_{pri}, w_o, w_v$, w_f , and w_{st} . For simplicity, let us assume that the time saved for each correct prediction is the same, i.e., $s_c = s_p = s_s =$ $s_{pri} = s_o = s_v = s_f = s_{st} = s$, and the time wasted for each wrong prediction is the same, i.e., $w_c = w_p = w_s =$ $w_{pri} = w_o = w_v = w_f = w_{st} = w$. Then, the net savings for OpenOffice, Netbeans, Eclipse, and Mozilla are $298045 \times s -$ $39307 \times w$, $297323 \times s - 45092 \times w$, $358063 \times s - 47049 \times w$, and $269939 \times s - 141301 \times w$, respectively. For OpenOffice, Netbeans, Eclipse, and Mozilla, when $s > 0.1319 \times w, s >$ $0.1614 \times w, s > 0.1314 \times w, and s > 0.5235 \times w,$ respectively, Im-ML.KNN could help save bug fixing time.

C. Impact of Default Assignment in Fixer Field

When a bug report is initially submitted, its fixer field could be assigned to a default address. For example, in OpenOffice, the fixer fields of some bug reports are set to "issues" when they are first submitted. It is easy to know that the fixer fields set to a default address will eventually get reassigned. Thus, we would like to investigate the effectiveness of Im-ML.KNN when we omit these default developer assignments.

To do so, we first remove bug reports whose fixers are initially set to default addresses. In OpenOffice and Netbeans, we remove bug reports whose fixers are initially set to default addresses such as "issues", "UNKNOWN", "spreadsheet", and "support". In Eclipse, we remove bug reports whose fixers are initially set to default addresses which end with "inbox". In Mozilla, we remove bug reports whose fixers are initially set to default addresses such as "nobody", "timeless", "accounts", and "bugzilla". In total, we have 35 934, 32 938, 12 801, and 11 416 bug reports remaining for OpenOffice, Netbeans, Eclipse, and Mozilla, respectively. We run Im-ML.KNN on these datasets, and denote the resultant results as Im – ML.KNN^{Default}.

| Projects | Component | Product | Severity | Priority |
|------------|--|---------------------------------------|---------------------------------------|---|
| OpenOffice | $38883 \times s_c - 3286 \times w_c$ | $39649 \times s_p - 2520 \times w_p$ | $41988 \times s_s - 181 \times w_s$ | $33544 \times s_{pri} - 8625 \times w_{pri}$ |
| Netbeans | $42232 \times s_c - 4113 \times w_c$ | $42624 \times s_p - 3721 \times w_p$ | 0 | $34001 \times s_{pri} - 12344 \times w_{pri}$ |
| Eclipse | $43917 \times s_o - 6722 \times w_o$ | $48251 \times s_v - 2388 \times w_v$ | $42327 \times s_s - 8312 \times w_s$ | $45257 \times s_{pri} - 5382 \times w_{pri}$ |
| Mozilla | $31085 \times s_c - 20320 \times w_c$ | $28524 \times s_p - 22881 \times w_p$ | $37982 \times s_s - 13423 \times w_s$ | $31016 \times s_{pri} - 20389 \times w_{pri}$ |
| | | | | |
| Projects | OS | Version | Fixer | Status |
| OpenOffice | $38615 \times s_o - 3554 \times w_o$ | $39019 \times s_v - 3150 \times w_v$ | $36044 \times s_f - 6125 \times w_f$ | $30303 \times s_{st} - 11866 \times w_{st}$ |
| Netbeans | $44471 \times s_o - 1874 \times w_o$ | $44302 \times s_v - 2043 \times w_v$ | $35671 \times s_f - 10674 \times w_f$ | $36022 \times s_{st} - 10323 \times w_{st}$ |
| Eclipse | $49174 \times s_{o} - 1465 \times w_{o}$ | $46390 \times s_v - 4249 \times w_v$ | $41531 \times s_f - 9108 \times w_f$ | $41216 \times s_{st} - 9423 \times w_{st}$ |

 $34582 \times \overline{s_v - 16823 \times w_v}$

TABLE XIII Cost of Im-ML.KNN

TABLE XIV

 $30298 \times s_o - 21107 \times w_o$

Mozilla

AVERAGE F-MEASURE OF IM-ML.KNN COMPARED WITH $Im - ML.KNN^{Default}$ USING TEN TIMES TENFOLD CROSS-VALIDATION SETUP. THE LAST ROW SHOW THE AVERAGE PERFORMANCE ACROSS THE FOUR PROJECTS

| Projects | Im-ML.KNN | Im-ML.KNN ^{Default} |
|------------|-----------|------------------------------|
| OpenOffice | 0.6204 | 0.5038 |
| Netbeans | 0.5963 | 0.5555 |
| Eclipse | 0.5597 | 0.5965 |
| Mozilla | 0.5796 | 0.5279 |
| Average. | 0.5890 | 0.5459 |

 TABLE XV

 Average F-Measure of IM-ML.KNN Compared With

 Im — ML.KNN^{Default} Using a Longitudinal Data Setup. The Last

 Row Show the Average Performance Across the 4 Projects

| Projects | Im-ML.KNN | Im-ML.KNN ^{Default} |
|------------|-----------|------------------------------|
| OpenOffice | 0.4187 | 0.4494 |
| Netbeans | 0.4848 | 0.4565 |
| Eclipse | 0.4154 | 0.4036 |
| Mozilla | 0.4708 | 0.3254 |
| Average. | 0.4474 | 0.4087 |

Tables XIV and XV present the average F-measure of Im-ML.KNN compared with Im-ML.KNN^{Default} using ten times tenfold cross-validation setup, and the longitudinal data setup, respectively. On average across the four projects, Im-ML.KNN^{Default} achieves average F-measures 0.5459 and 0.4087 in the cross validation setup and longitudinal data setup respectively. We notice the average F-measures of Im – ML.KNN^{Default}, but the differences are relatively small (i.e., <0.05).

From the intution, removing the bug reports whose fixer fields are set to a default address may remove the bug reports submitted by users, and leave the reports that were created by developers, since the developers are the ones with the project knowledge to assign to something other than default. We also investigate whether it is the case. For example, in OpenOffice, we find a developer Frank Schonheit has reported 1150 bug reports, and fixed 146 bug reports. However, still seven out of the 1150 reported bugs are assigned to the default address "issue". Also, a user deye only has reported one bug report 102816, but the fixer field is set to "ab@bregas.de" initially. Thus, users and developers in the community all have the chance to set the fixer field to a default address.

D. Evaluation

 $38780 \times s_f - 12625 \times w_f$

In this paper, we automatically identify good α , β , γ , and *threshold*_l values for *Im-ML.KNN* following the algorithm presented in Fig. 1. The values are optimized (and thus are different) for different datasets and different training frames in our tenfold cross-validation and longitudinal data setup.

 $37673 \times s_{st} - 13732 \times w_{st}$

Also, for each label l, which corresponds to a type of bug report field reassignment, our *Im-ML.KNN* automatically identify good *threshold*_l from the training bug reports. Thus, the decision boundaries (aka. thresholds) of *Im-ML.KNN* are fixed, i.e., the precision and recall would not be varied with different threshold values. We believe our *Im-ML.KNN* could help developers to use our tool in practice, since they do not need to consider the effect of the threshold values to the performance of our tool.

In single-label learning literature, receiver operating characteristic (ROC) curve is a graphical plot which shows the performance of a binary classifier when its threshold is varied [34]. Notice in our paper, we do not analyze the ROC curve due to three reasons, given here.

- *Im-ML.KNN* automatically identifies good thresholds for each of the eight types of field reassignment, which makes the thresholds fixed. Thus, there is only one point in the ROC curve for each of the eight types of field reassignment.
- In multilabel learning literature, ROC curve is rarely used to evaluate the performance of a multi-label learning algorithm, see [13], [26]–[28]. Normally, researchers prefer to use precision, recall, and F-measure to measure the performance of a multilabel learning algorithm.
- In our paper, there are in total eight types of field reassignment, which correspond to eight labels. If for each label, we plot its ROC curve, then there would be too many curves.

E. Im-ML.KNN Versus HOMER-KNN

In the previous section, we used Naive Bayes as the underlying classifier for HOMER, which is also used by Tsoumakas *et al.* [15]. We notice HOMER could also use other underlying classifiers. Thus, we also use kNN as the underlying classifier of HOMER (denoted as HOMER-KNN) as we do in *Im-ML. KNN*, and we set the number of neighbors in kNN as 10 as *Im-ML.KNN*.

Table XVI and XVII present the average F-measure of Im-ML.KNN compared with HOMMER-KNN using ten times tenfold cross-validation setup and longitudinal data setup,

| USING TENFOLD CROSS-VALIDATION SETUP. THE LAST ROW SHOW | THE |
|---|-----|
| AVERAGE PERFORMANCE ACROSS THE FOUR PROJECTS | |
| | |

| Projects | Im-ML.KNN | HOMER-KNN | Impovement. |
|------------|-----------|-----------|-------------|
| OpenOffice | 0.6204 | 0.5974 | 3.85% |
| Netbeans | 0.5963 | 0.5409 | 10.24% |
| Eclipse | 0.5597 | 0.5309 | 4.44% |
| Mozilla | 0.5796 | 0.5667 | 2.28% |
| Average. | 0.5890 | 0.5602 | 5.20% |

TABLE XVII Average F-Measure of IM-ML.KNN Compared With HOMER-KNN Using a Longitudinal Data Setup. The Last Row Show the Average Performance Across the Four Projects

| Projects | Im-ML.KNN | HOMER-KNN | Improvement. |
|------------|-----------|-----------|--------------|
| OpenOffice | 0.4187 | 0.3851 | 8.71% |
| Netbeans | 0.4848 | 0.4300 | 12.73% |
| Eclipse | 0.4154 | 0.3905 | 6.37% |
| Mozilla | 0.4708 | 0.4245 | 10.93% |
| Average. | 0.4474 | 0.4075 | 9.68% |

respectively. From Table XVI, we note that the improvement of our method over HOMER-KNN is substantial. We improve the average F-measure of HOMER-KNN by 3.85%, 10.24%, 4.44%, and 2.28% for OpenOffice, Netbeans, Eclipse, and Mozilla, respectively. Averaging across the four datasets, the average improvement achieved by *Im-ML.KNN* is 5.20% in the tenfold cross-validation setup. From Table XVII, We improve the average F-measure of HOMER-KNN by 8.71%, 12.73%, 6.37%, and 10.93% for OpenOffice, Netbeans, Eclipse, and Mozilla, respectively. Averaging across the four datasets, the average improvement achieved by *Im-ML.KNN* is 9.68% in the longitudinal data setup.

F. Qualitative Analysis

Here, we perform a qualitative analysis on why the features that we consider are relevant, how our *Im-ML.KNN* could potentially help reduce bug fixing time, and why we need to combine the 3 classifiers. We take status reassignment and refinement (i.e., a bug report is reopened) and component reassignment and refinement and refinementas examples.

Features: Tables XVIII–XXI present bug reports from Netbeans. These four bug reports are chose from the prediction results of our Im-ML.KNN, Lamkanfi *et al.*'s, ML.KNN, and HOMER-NB. Also, since our Im-ML.KNN is a nearest neighbor based approach, it would be easy to explain why our approach outperforms the baseline approaches if some fields of the bug reports are similar. Note that we record the values of fields in these bug reports when they are first reported—before any reassignments and refinements (if any). The status and component fields in these 4 bug reports get reassigned and refined. We notice there are many similarities among these four bug reports.

• Many values of meta features in these 4 bug reports are the same. For example, the product, component, assignee, and version fields for these 4 bug reports are "db", "UI", "davidvc", and "6.X", respectively. Also, for bug report #137543 and #149041, their reporter are the same, i.e., "Roman Mostyka".

TABLE XVIIIBUG REPORT #137543 OF NETBEANS

| Summary: | Red information message in "New Database Connec- | |
|--------------|---|--|
| | tion" dialog | |
| Description: | According http://wiki.netbeans.org/InformationIcons | |
| | 1. Start IDE. Open "Services" window. | |
| | 2. Rightclick "Databases" node and choose "New Con- | |
| | nection". | |
| | Result: "New Database Connection" dialog appears with | |
| | "Please specify a value for the required field Database:" | |
| | message in the bottom. This message is RED and looks | |
| | like error message. View will be better if message is | |
| | not red (probably just black). | |
| Product: | db | |
| Component: | UI | |
| Reporter: | Roman Mostyka | |
| Assignee: | davidvc | |
| Version: | 6.X | |
| Priority: | P4 | |
| Platform: | ALL | |
| OS: | Windows XP | |

TABLE XIXBUG REPORT #137600 OF NETBEANS

| Summary: | I18N - some driver names in New Connection dialog | |
|--|--|--|
| | drop-down not localized | |
| Description: | using new db connection dialog, the word Host does | |
| | not come from the pseudo localized bundle file - the | |
| | word host is in these bundles, but its not coming from | |
| | the localized bundle as is all the other labels. | |
| | this label is in bundle file org-netbeans-modules- | |
| | db/NewConnectionHost =&Host: | |
| Product: | db | |
| ~ | | |
| Component: | UI | |
| Component: Reporter: | UI Ken Frank | |
| Component: Reporter: Assignee: | UI Ken Frank davidvc | |
| Component: Reporter: Assignee: Version: | UI Ken Frank davidvc 6.X | |
| Component: Reporter: Assignee: Version: Priority: | UI Ken Frank davidvc 6.X P2 | |
| Component: Reporter: Assignee: Version: Priority: Platform: | UI Ken Frank davidvc 6.X P2 ALL | |

TABLE XXBUG REPORT #144020 OF NETBEANS

| Summary: | Ugly New Database connection dialog UI |
|--------------|--|
| Description: | Please, fix all UI issues in New Database connection |
| | dialog like, incorrect alignment of UI components, |
| | the size of components, spacing, See the attached |
| | screenshot. |
| Product: | db |
| Component: | UI |
| Reporter: | Petr Blaha |
| Assignee: | davidvc |
| Version: | 6.X |
| Priority: | P3 |
| Platform: | ALL |
| OS: | ALL |

• The description of these four bug reports are similar, i.e., their textual features are similar. These four bug reports are all about UI issues and they share some common terms, such as "dialog" and "connection."

From the observation, we notice that if we consider both the meta and textual features, the performance of *Im-ML.KNN* could be further improved.

Reducing Bug Fixing Time: Notice that bug report #149041 in Table XXI takes a long time to be fixed. It is created in "2008-10-03" and is only fixed in "2009-05-12". The bug fixing time is more than half a year. The component and status fields

TABLE XXIBUG REPORT #149041 OF NETBEANS

| Summary: | Wrong size for some fields in created table | |
|--------------|---|--|
| Description: | 1. Connect to "travel" Java DB. | |
| | 2. Rightclick "Tables" and choose "Create Table". | |
| | 3. Set table name, column name, choose INTEGER | |
| | type, set size to 3 and press "OK". | |
| | Result: Table with column is created, but size of column | |
| | is 10, not 3 as it was set. I guess it can be true not only | |
| | for INTEGER type. | |
| Product: | db | |
| Component: | UI | |
| Reporter: | Roman Mostyka | |
| Assignee: | davidvc | |
| Version: | 6.X | |
| Priority: | P3 | |
| Platform: | ALL | |
| OS: | ALL | |
| Creation | 2008-10-03 | |
| Date: | | |
| Fixed Date: | 2009-05-12 | |

of this bug report are reassigned and refined. These reassignments and refinements mean that the component that this bug affects is wrongly reported (which leads to the component reassignment) and the bug is initially fixed incorrectly and needs to be re-fixed (which leads to status reassignment). These reassignments and refinements are likely to increase bug fix time. If our system is deployed, it can predict that the component field is likely to be reassigned and refined, and the bug report is likely to be reopened (which implies that the bug is hard-to-fix). This can guide developers to first find the right component before attempting to fix the bug, and to be more careful in performing the fix, as the fix is likely to be a risky one. As a result, the bug fixing time is likely to be reduced. Note that the model building time for our Im-ML.KNN is only several hours at most (and it could be trained offline), and the typical prediction time for a bug report is less than a second. Thus, from developers' point of view, they can get alert information in just less than a second.

Composing Classifiers: Note that we have three classifiers in Im-ML.KNN, and the prediction results for the 3 classifiers could be different. The combination of these three classifiers could utilize the advantages of each classifier, and achieve a better performance. For example, if we predict the fields which would get reassigned and refined for bug report #149041, we notice that the meta features for #149041 are very similar to the other three bug reports (#137543, #137600, and #144020), however its textual features are less similar to the other three bug reports. Thus, the meta classifier predicts that the component and status fields would get reassigned and refined; on the other hand, the textual classifier does not predict any of these two fields would get reassigned and refined, while the mixed classifier predicts that only the component field would get reassigned and refined. By combining these three classifiers, *Im-ML.KNN* predicts that the component and status fields of bug report #149041 would get reassigned and refined.

VIII. THREATS TO VALIDITY

Here, we highlight threats to internal validity, external validity, and construct validity.

Threats to Internal Validity: Threats to internal validity relate to bias and errors in our experiments. To reduce the risk of this threat, we have double checked our datasets and our experiments, however there could still be errors that we did not notice. Also, to reduce training set selection bias, we have applied tenfold cross validation ten times and recorded the average performance. And we have also evaluated Im-ML.KNN using the longitudinal data setup.

Threats to External Validity: Threats to external validity relate to the generalizability of our results. To reduce this risk, we have analyzed 190558 closed and fixed bug reports from four open source software projects, and investigate eight types of bug report field reassignment. Analyzing a substantial proportion of bug reports in selected projects is important for the generalizability of the findings. Past studies also only investigate similar number of bug reports from these projects [33], [35]–[38]. In the future, we plan to reduce this threat further by analyzing more bug reports from more software projects, including commercial and open source projects.

Threats to Construct Validity: Threats to construct validity refer to the suitability of our evaluation measures. We use the average F-measure score as the main evaluation metric which is also used by past studies to evaluate the effectiveness of a prediction technique in various software engineering studies [20], [22], [31], [39]. Thus, we believe there is little threat to construct validity.

IX. RELATED WORK

In this section, we briefly review studies on bug report field reassignments in Section IX-A, and multilabel learning in software engineering in Section IX-B.

A. Bug Report Field Reassignment

The most related work to our paper is the empirical study we perform [9]. In the empirical study, we analyze the root causes of bug report field reassignment by sending emails to developers in open source software projects. We also analyze various field reassignments that happen in 190 558 bug reports in four open-source software projects. We find that approximately 80% of the bug reports have one or more of their fields reassigned, and the bug reports whose fields get reassigned require more time to be fixed than those without field reassignments. This work complements our previous work, and our previous work serves as a motivation to this work. In particular, in this paper we propose an automated tool to predict which bug report fields would get reassigned, to help developers reduce bug fixing effort.

There have been a number of other studies on bug report field reassignments. Guo *et al.* perform an empirical study on fixer reassignments, and they find five primary reasons for fixer reassignments, i.e., difficulty to identify the root cause, ambiguous ownership of components, poor bug report quality, difficulty to determine the proper fix, and workload balancing [40]. Jeong *et al.* investigate fixer reassignments in Mozilla and Eclipse, and they propose a method which uses fixer reassignment graph to improve the performance of bug triaging [7]. Bhattacharya *et al.* extend Jeong *et al.*'s work to improve the accuracy of bug triaging by using multi-feature fixer reassignment graph [33]. Shihab *et al.* study reopened bugs in Eclipse, Apache HTTP, and OpenOffice, and find that the average time to resolve a reopened

bug is approximately twice as much as the time to resolve a nonreopened bug [4], [5]. They propose a machine learning based method to predict reopened bug reports; they extract four groups of features, related to work habits, bug report fields, bug fix, and people, containing a total of 24 features. Sureka investigates the component reassignment problem in Eclipse and Mozilla, and proposes the use of machine learning algorithms to predict the components of bug reports [12]. Lamkanfi et al. also study the component reassignment problem, and find that the proportion of bug reports whose component field gets reassigned varies between 8.3% to 32.7% in Eclipse and Mozilla [6]. They propose the usage of Naive Bayes to predict whether the component of a bug report would be reassigned, and their method achieves precision and recall between 0.58-0.94 and 0.54-1 for bug reports of several products of Eclipse and Mozilla. Our work generalizes the above studies; whereas previous studies focus on single bug report field reassignment, our work considers all field reassignments simultaneously.

B. Multilabel Learning

There have been a number of studies on multi-label learning in software engineering [20], [21], [36], [41]. Xia et al. propose *TagCombine* to recommend tags in software information sites [21]. Xia et al. propose DevRec to recommend bug resolvers [36]. Each of these two studies makes use of a multi-label learning algorithm. Banerjee et al. propose the usage of multi-label learning algorithms to select suitable duplicated bug report detection techniques, and combine them to achieve a better performance [41]. Xia et al. propose a composite method MLL-GA which combines different multi-label learning algorithms by leveraging genetic algorithms, to achieve a better performance for software behavior learning [20]. Our work is orthogonal to the above studies since we study a different problem-we focus on predicting which bug report fields would get reassigned rather than recommending a set of tags, resolvers, and duplicated bug report detection techniques, and predicting the fault types of a failure. Also, different from the above studies, in this study we consider the class imbalance problem, and adapt ML.KNN to handle this problem.

X. CONCLUSION AND FUTURE WORK

In this paper, we develop a tool which leverages *multi-label learning* algorithms to automatically predict which *bug report* fields would be reassigned and refined. We propose imbalanced ML.KNN (Im-ML.KNN), which extends ML.KNN, by considering the class imbalance phenomenon. Im-ML.KNN is a composite model, which combines three multilabel classifiers built on different types of features (i.e., meta, textual, and mixed features). We evaluate the performance of *Im-ML.KNN* on four large-scale open source projects which contain 190 558 bug reports in total. Experiment results show that Im-ML.KNN could achieve an average F-measure score of 0.56-0.62. We also compare Im-ML.KNN with other state-of-art methods, such as the method proposed by Lamkanfi et al., ML.KNN, and HOMER. The results show that Im-ML.KNN on average improves the average F-measure scores of Lamkanfi et al.'s method, ML.KNN, and HOMER-NB by 119.69%, 9.11%, and 161.08%, respectively. We show that the performance of Im-ML.KNN remains

relatively stable across a wide range of parameter settings thus showing that it is not sensitive on the optimal setting of its parameter.

In the future, we plan to evaluate *Im-ML.KNN* with more bug reports from more software projects and develop a better technique which could improve the bug report field reassignment and refinement prediction further.

REFERENCES

- M. Newman, "Software errors cost us economy \$59.5 billion annually," NIST Assesses Technical Needs of Industry to Improve Software-Testing, 2002.
- [2] T. Zimmermann, R. Premraj, N. Bettenburg, S. Just, A. Schroter, and C. Weiss, "What makes a good bug report?," *IEEE Trans. Software Eng.*, vol. 36, no. 5, pp. 618–643, Sep.–Oct. 2010.
- [3] T. Zimmermann, R. Premraj, J. Sillito, and S. Breu, "Improving bug tracking systems," in *Proc. 31st Int. Conf. Software Eng.-Companion* Vol., 2009, pp. 247–250.
- [4] E. Shihab, A. Ihara, Y. Kamei, W. M. Ibrahim, M. Ohira, B. Adams, A. E. Hassan, and K.-I. Matsumoto, "Predicting re-opened bugs: A case study on the eclipse project," in *Proc. 17th Working Conf. Reverse Eng.*, 2010, pp. 249–258.
- [5] E. Shihab, A. Ihara, Y. Kamei, W. M. Ibrahim, M. Ohira, B. Adams, A. E. Hassan, and K.-I. Matsumoto, "Studying re-opened bugs in open source software," *Empirical Software Eng.*, pp. 1–38, 2012.
- [6] A. Lamkanfi and S. Demeyer, "Predicting reassignments of bug reports-an exploratory investigation," in *Proc. 17th Eur. Conf. Software Maintenance and Reeng.*, 2013, pp. 327–330.
- [7] G. Jeong, S. Kim, and T. Zimmermann, "Improving bug triage with bug tossing graphs," in Proc. 7th Joint Meeting Eur. Software Eng. Conf. and the ACM SIGSOFT Symp. The Foundations of Software Eng., 2009, pp. 111–120.
- [8] R. K. Saha, S. Khurshid, and D. E. Perry, "An empirical study of long lived bugs," in *Proc. IEEE Conf. Software Maintenance, Reeng. and Reverse Eng.*, 2014, pp. 144–153.
- [9] X. Xia, D. Lo, M. Wen, E. Shihab, and B. Zhou, "An empirical study of bug report field reassignment," in *Proc. IEEE Conf. Software Maintenance, Reeng. and Reverse Eng.*, 2014, pp. 174–183.
- [10] S. Mani, S. Nagar, D. Mukherjee, R. Narayanam, V. S. Sinha, and A. A. Nanavati, "Bug resolution catalysts: Identifying essential non-committers from bug repositories," in *Proc. 10th Working Conf. Mining Software Repositories*, San Francisco, CA, USA, 2013, pp. 193–202.
- [11] G. Tsoumakas and I. Katakis, "Multi-label classification: An overview," *Int. J. Data Warehousing and Mining*, vol. 3, no. 3, pp. 1–13, 2007.
- [12] A. Sureka, "Learning to classify bug reports into components," in *Objects, Models, Components, Patterns.* Berlin, Germany: Springer, 2012, pp. 288–303.
- [13] M.-L. Zhang and Z.-H. Zhou, "Ml-knn: A lazy learning approach to multi-label learning," *Pattern Recognition*, vol. 40, no. 7, pp. 2038–2048, 2007.
- [14] H. He and E. A. Garcia, "Learning from imbalanced data," *IEEE Trans. Knowl. Data Eng.*, vol. 21, no. 9, pp. 1263–1284, Sep. 2009.
- [15] G. Tsoumakas, I. Katakis, and I. Vlahavas, "Effective and efficient multilabel classification in domains with large number of labels," in *Proc. ECML/PKDD Workshop on Mining Multidimensional Data*, 2008, pp. 30–44.
- [16] J. Anvik, L. Hiew, and G. C. Murphy, "Who should fix this bug?," in Proc. 28th Int. Conf. Software Eng., 2006, pp. 361–370.
- [17] R. A. Baeza-Yates and B. A. Ribeiro-Neto, Modern Information Retrieval 2011.
- [18] A. Tamrawi, T. T. Nguyen, J. M. Al-Kofahi, and T. N. Nguyen, "Fuzzy set and cache-based approach for bug triaging," in *Proc. 19th ACM SIGSOFT Symp. and 13th Eur. Conf. Foundations of Software Eng.*, 2011, pp. 365–375.
- [19] J. Han, M. Kamber, and J. Pei, Data Mining: Concepts and Techniques. San Mateo, CA, USA: Morgan Kaufmann, 2006.
- [20] X. Xia, Y. Feng, D. Lo, Z. Chen, and X. Wang, "Towards more accurate multi-label software behavior learning," in *Proc. IEEE Conf. Software Maintenance, Reeng. and Reverse Eng.*, 2014, pp. 134–143.
- [21] X. Xia, D. Lo, X. Wang, and B. Zhou, "Tag recommendation in software information sites," in *Proc. 10th Int. Workshop on Mining Soft*ware Repositories, 2013, pp. 287–296, IEEE Press.

- [22] Y. Tian, J. Lawall, and D. Lo, "Identifying linux bug fixing patches," in Proc. 34th Int. Conf. Software Eng., 2012, pp. 386–396.
- [23] T. Menzies and A. Marcus, "Automated severity assessment of software defect reports," in *Proc. IEEE Int. Conf. Software Maintenance*, 2008, pp. 346–355.
- [24] F. Thung, D. Lo, and J. L. Lawall, "Automated library recommendation," in *Proc. WCRE*, 2013, pp. 182–191.
- [25] G. Tsoumakas, E. Spyromitros-Xioufis, J. Vilcek, and I. Vlahavas, "Mulan: A Java library for multi-label learning," *J. Mach. Learning Res.*, vol. 12, pp. 2411–2414, 2011.
- [26] G. Tsoumakas, I. Katakis, and L. Vlahavas, "Random k-labelsets for multilabel classification," *IEEE Trans. Knowl. Data Eng.*, vol. 23, no. 7, pp. 1079–1089, Jul. 2011.
- [27] J. Read, B. Pfahringer, G. Holmes, and E. Frank, "Classifier chains for multi-label classification," *Machine Learning*, vol. 85, no. 3, pp. 333–359, 2011.
- [28] M. Zhang and Z. Zhou, "A review on multi-label learning algorithms," *IEEE Trans. Knowl. Data Eng.*, vol. 26, no. 8, pp. 1819–1837, Aug. 2014.
- [29] Y. Feng and Z. Chen, "Multi-label software behavior learning," in Proc. Int. Conf. Software Eng., 2012, pp. 1305–1308.
- [30] R. Wu, H. Zhang, S. Kim, and S.-C. Cheung, "Relink: Recovering links between bugs and changes," in *Proc. 19th ACM SIGSOFT Symp. and* 13th Eur. Conf. Foundations of Software Eng., 2011, pp. 15–25.
- [31] A. T. Nguyen, T. T. Nguyen, H. A. Nguyen, and T. N. Nguyen, "Multilayered approach for recovering links between bug reports and fixes," in *Proc. ACM SIGSOFT 20th Int. Symp. Foundations of Software Eng.*, 2012, p. 63.
- [32] F. Peters and T. Menzies, "Privacy and utility for defect prediction: Experiments with morph," in *Proc. 34th Int. Conf. Software Eng.*, 2012, pp. 189–199.
- [33] P. Bhattacharya and I. Neamtiu, "Fine-grained incremental learning and multi-feature tossing graphs to improve bug triaging," in *Proc. IEEE Int. Conf. Software Maintenance*, 2010, pp. 1–10.
- [34] T. Fawcett, "An introduction to roc analysis," Pattern Recognition Lett., vol. 27, no. 8, pp. 861–874, 2006.
- [35] P. Hooimeijer and W. Weimer, "Modeling bug report quality," in Proc. 22nd IEEE/ACM Int. Conf. Automated Software Eng., 2007, pp. 34–43.
- [36] X. Xia, D. Lo, X. Wang, and B. Zhou, "Accurate developer recommendation for bug resolution," in *Proc. 20th Working Conf. Reverse Eng.*, 2013, pp. 72–81.
- [37] S. Zaman, B. Adams, and A. E. Hassan, "Security versus performance bugs: A case study on Firefox," in *Proc. 8th Working Conf. Mining Software Repositories*, 2011, pp. 93–102.
- [38] X. Xia, D. Lo, E. Shihab, X. Wang, and B. Zhou, "Automatic, high accuracy prediction of reopened bugs," *Automated Software Eng.*, pp. 1–35, 2014.
- [39] J. Nam, S. J. Pan, and S. Kim, "Transfer defect learning," in Proc. Int. Conf. Software Eng., 2013, pp. 382–391.
- [40] P. J. Guo, T. Zimmermann, N. Nagappan, and B. Murphy, "Not my bug! and other reasons for software bug report reassignments," in *Proc. ACM Conf. Comput. Supported Cooperative Work*, 2011, pp. 395–404.
- [41] S. Banerjee, Z. J. Syed, J. Helmick, and C. Bojan, "A fusion approach for classifying duplicate problem reports," in *Proc. ISSRE*, 2013, pp. 208–217.

Xin Xia (M'14) received the Ph.D. degree from the College of Computer Science and Technology, Zhejiang University, Hangzhou, China, in 2014.

He is currently a Research Assistant Professor with the College of Computer Science and Technology, Zhejiang University, Hangzhou, China. His research interests include software analytic, empirical study, and mining software repository.

David Lo (M'14) received the Ph.D. degree from the National University of Singapore, Singapore, in 2008.

He is currently an Assistant Professor with the School of Information Systems, Singapore Management University, Singapore. He has close to 10 years of experience in software engineering and data mining research and has authored and coauthored more than 130 publications in these areas.

Dr. Lee was the recipient of the Lee Foundation Fellow for Research Excellence from the Singapore Management University in 2009. He has won a number of research awards including an ACM distinguished paper award for his work on bug report management. He has also served on the program committees of ICSE, ASE, KDD, VLDB, and many others. He is a steering committee member of the IEEE International Conference on Software Analysis, Evolution, and Reengineering (SANER) which is a merger of the two major conferences in software engineering, namely CSMR and WCRE. He will also serve as the general chair of ASE 2016. He is a leading researcher in the emerging field of software analytics and has been invited to give keynote speeches and lectures on the topic in many venues, such as the 2010 Workshop on Mining Unstructured Data, the 2013 Gnie Logiciel Empirique Workshop, the 2014 International Summer School on Leading Edge Software Engineering, and the 2014 Estonian Summer School in Computer and Systems Science.

Emad Shihab received the B.Eng. and M.A.Sc. degrees from the University of Victoria, Victoria, BC, Canada, and the Ph.D. degree from Queen's University, Kingston, ON, Canada.

He is an Assistant Professor with the Department of Computer Science and Software Engineering, Concordia University, Montreal, QC, Canada. His research interests are in software engineering, software quality assurance, empirical software engineering, mining software repositories, mobile applications and software architecture. He was a Software Research Intern with Research In Motion, Waterloo, ON, Canada, and Microsoft Research, Redmond, WA, USA.

Dr. Shihab held an NSERC Alexander Graham Bell Canada Graduate Scholarship (CGS-D3) and the PhD research achievement award from the School of Computing at Queens University. He served as organizer to a number of events related to Mining Software Repositories (MSR) and Mobile Applications, including serving as program chair of the MSR 2012 Challenge Track and the MSR 2013 Data Showcase Track. Dr. Shihab regularly serves on the programming committee of Software Engineering conferences and journals such as ICSME, MSR, ICPC, SANER (formerly WCRE/CSMR), OSS, TSE and EMSE.

Xinyu Wang received the B.S. and Ph.D. degrees in computer science from Zhejiang University, Hangzhou, China, in 2002 and 2007, respectively.

He was a Research Assistant with Zhejiang University, Hangzhou, China, during 2002–2007. He is currently an Associate Professor with the College of Computer Science, Zhejiang University, Hangzhou, China. His research interests include software engineering, formal methods, and very large information systems.